Technical Data Sheet

TDS B7649 Anaerobic Activator Revised 03.08.10



Bondloc B7649 Anaerobic Activator

PRODUCT DESCRIPTION

B7649 speeds cure of all Anaerobic fluids and pastes and extends cure through volume. B7649 helps fixture time and reduces ultimate cure time. Use B7649 when materials are inactive (plastics or passivated matals) or where temperature is under 15°C.

APPLICATIONS

- Activates Anaerobic adhesives
- Accelerates cure time
- Recommended for passive metals or inert surfaces

INSTRUCTIONS FOR USE

Spray or brush activator onto either both or one surface. It may be necessary to treat both surfaces in the case of big gaps or where more activity is required. In the case of B7649 allow solvent to evaporate and dry. Parts should be bonded as soon as possible, but activators kept in clean conditions will last up to 30 days. Next assemble by applying adhesive to one or both surfaces and apply firm pressure for 30 - 40 seconds without movement.

Parts will have a handling strength usually within 20 - 30 minutes, but full strength can take up to 12 - 24 hours depending on conditions and metals activity.

TECHNICAL FEATURES

Solvent	Heptane Based
Evapouration	60 seconds
Flammability	Flammable

HEALTH & SAFETY IN USE

No chronic toxic effects. See MSDS for full details.