

RAPID RESPONSE PATROL BOAT



PERFORMANCE & SAFETY

DESIGNED FOR:

- Maximum safety and comfort
- Excellent performance and maneuverability
- Durable, rugged construction
- Minimum maintenance costs and associated
 downtime
- High overall value
- Long service life
- Ability to be customized

PARTICULARS:

- Length: 29' 4" (hull)
 - 32' 2" (incl. platform)
- Beam: 10' 5"
- Draft: 18"
- Deadrise: 20 deg transom
- Propulsion: Volvo D6 370 hp
 Ultradynamics 305 waterjet
- Fuel: 100 I Gallons (454 L)





Designed and manufactured by ABCO



SPECIFICATIONS for ABCO 29 DJ (DIESEL JET)	Heating and Defrosting:
The ABCO 29 DJ is designed for safety and performance in harbor	• Hot water bus heater with fan
patrol, search and rescue, and emergency missions.	Battery and Electrics:
H II Standard	• Two AGM batteries with battery boxes
Hull Structure:Hard chine hull with chine flats	Battery selector switches
 Lifting strakes/spray deflectors 	• 10 circuit 12VDC breaker panel
 Three main watertight hull compartments 	Battery charger and shore power
 Closed wheelhouse and cuddy 	• 4 - 120 VAC outlets
 Heavy duty internal structure with longitudinal stringers and 	
bulkheads	 Windows, doors, hatches: Two forward facing windows and two side sliding windows of
• Self bailing deck through freeing ports	safety glass set in aluminum frames
• Raised pattern main deck, washboards, foredeck	 Open companionway to cuddy
• 7 welded cleats	 Two windshield wipers with washer system for forward facing
• Forward anchor rode locker	windows
• Double horizontal safety bow rail extending aft approximately 12	• 19" Bomar hatch on cuddy top
feet from bow	• Hinged lexan full view door, lockable
• Transom platform / jet guard	• Engine 'day' hatch with 2" marine seating cushion
• Tough 6" proprietary "epsilon" non marking fendering system	 Large engine maintenance hatch
• Sound insulation in engine compartment held in place by perforated	
galvanized steel	Lighting:
	Navigation lights
Wheelhouse, Cuddy:	• Interior lights (red/white)
• Wheelhouse approximately 6'6" long from back to console	Halogen aft deck light
• Hinged watertight lexan full view door, lockable	• Blue police light
• Minimum headroom wheelhouse 6'5"	
Raised cuddy approximately 8' long	Fire Fighting:
• Mounting frame for radar, lights, antennas and horn	• 2 - 5 # ABC fire extinguisher, wheelhouse
• Safety handrail full length on top, both sides and after sides of	• 1 - 5# ABC fire extinguisher, engine compartment
 house Head, sink and seats with marine cushions in cuddy 	 1 - 10 lb. CO2 fire extinguisher for engine room Smoke alarm and heat rise alarm for engine compartment
rieud, shin and seals whit marine easilons in eaddy	• Smoke alarm and near fise alarm for engine compartment
Propulsion:	Navigation , Communication:
 Volvo D6 370 hp electronic diesel with ZF reverse gear 	RayMarine DSC VHF with 8 foot antennae
• Ultra Dynamic 305 waterjet	• Integrated Raymarine Multi function C80 radar/gps/sounder/plotter
• CV driveshaft	with 8'display and 18" radome with electronic charts for Nova
• Wet exhaust with muffler	Scotia
	Ritchie navigator compass
Steering:	Single trumpet electric horn
• Hydraulic steering with stainless steel wheel	Ground tackle, dock lines:
Helm pump sized for waterjet application	• 16 # Danforth style galvanized anchor with 10 feet 5/16"
Fuel System:	galvanized chain and 150 feet 5/8" twist nylon rode
 Separate fuel tank - 100 Imperial Gallons (454 litres) 	 Four 30 foot 5/8" twist nylon dock lines
 Tank and fuel system pressure tested and certified 	
 Racor filtration system 	Finish:
 Emergency fuel shutoff located on tank discharge 	• Interior - insulated with laminate cover
 Electric fuel gauge mounted on console 	• Bottom - antifouling with coloured boottop
• Fuel fill catch all	• Topsides - bare aluminum or optional painting
	Miscellaneous:
Pumps and Plumbing:	Zinc anodes
• One 4000GPM and two 1250 GPM Rule bilge pumps with automatic activators and dedicated dash mounted panel with	 Life jackets, flares, and life ring
audible alarm	 Safety plaques and signage
One hand bilge pump	Owners manual
 Manual head in cuddy with 13 USG holding tank 	 Customization and optional equipment available
• Sink with manual pump and 13 USG fresh water tank	May 2008 - Subject to change without notice
Way 2000 - Subject to change without notice	
ABCO Industries Limit	ted Telephone: 902-634-8821

ABCO

ABCO Industries Limited P.O. Box 1120, 81 Tannery Road Lunenburg, NS Canada B0J 2C0

Telephone: Toll Free: Fax: Email: Web:

902-634-8821 866-634-8821 902-634-8583 info@abco.ca www.abco.ca