

InfoTech™

Last Revision Date: July 2006
Supersedes: April 1999

PLIOBOND® 20 General-Purpose Adhesive

GENERAL-PURPOSE ADHESIVE

DESCRIPTION: PLIOBOND 20 adhesive is a general-purpose thermosetting adhesive that can be used to bond virtually all porous and nonporous substrates. When cured, PLIOBOND 20 adhesive provides tough, chip resistant bonds that remain flexible over a wide temperature range. Substrates bonded with PLIOBOND 20 adhesive offer excellent resistance to mechanical shock and oxidization. This adhesive provides outstanding dielectric properties and has low water absorption. PLIOBOND 20 adhesive comes ready to use; no conditioner, accelerator, or catalyst is required.

SUGGESTED USES: PLIOBOND 20 adhesive can be used as a sealer, primer, water repellent, or coating for metal, wood, plastic, plastic film, ceramic, bone, ivory, glass, rubber, paper, leather, plaster, drywall, insulation, concrete, brick, and stone. Other applications include:

- Assembling electrical appliances and equipment.
- Doping electric motor armature coils.
- Anchoring nonskid material to floors.
- Waterproofing awnings, tarps, convertible tops, and outdoor furniture.
- Protecting above-water surfaces on watercraft.

ALTERNATE PRODUCTS: PLIOBOND 30 and PLIOBOND 40 adhesives have higher solids and viscosity. PLIOBOND 1000 is a low-odor version.

TYPICAL LIQUID PROPERTIES AT 77 °F	
Base	Synthetic Rubber
Color	Tan
Solids by Weight, %	21 ± 2
Solvent Formulation	Ketone
Viscosity, cps Brookfield RVT Spindle No. 2 at 20 rpm	800 ± 400
Specific Gravity	0.868
Pounds per Gallon	7.23
Flash Point, °F (SETA)	20
Coverage	215-230 sq ft/gal/dry mil
Application Temperature, °F	40-100
Service Temperature, °F	ASTM D-816-10 psi at 500°F for 1 hour

* Typical Values: Based on material tested in our laboratories but varies from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

©Ashland, 1999, 2006
Ashland Inc., Specialty Polymers & Adhesives • PO Box 2219 • Columbus, OH 43216 • Tel: 1.800.322.6580 – Customer Service • Tel: 1.614.790.3333 • Fax: 1.614.790.3206



Ashland is committed to the continuous evolution of technology and service solutions that promote health, safety and environmental protection around the world.

Responsible Care®

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.

™ & ® Trademark and Registered Trademark, Ashland • Responsible Care and the Responsible Care Logo are registered service marks of the American Chemistry Council, the Canadian Chemical Producers' Association and of other entities in other countries.

ASHLAND®

PLIOBOND® 20
General-Purpose Adhesive

Page 2

METHOD OF APPLICATION: PLIOBOND 20 adhesive can be applied by spraying, roll coating, knife coating, or brushing.

HANDLING: PLIOBOND 20 adhesive contains ingredients that could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. All five-gallon pails and larger metal containers should be grounded and/or bonded when material is transferred. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use a welding or cutting torch on or near drum (even empty) because product (even residue) can ignite explosively.

Ashland maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers.

Our Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Ashland products in your facilities.

RECOMMENDED STORAGE: When PLIOBOND 20 adhesive is stored indoors, out of direct sunlight, and in the original, unopened container between 60 °F and 80 °F, the shelf life is six months. Always rotate stock.

DOT Label Required: Flammable Liquid

CODE: 584004

