



XCE 1012 COVER

- NOTES:
1. MINIMUM SPACING FROM CENTER OF OPERATOR TO NEAREST FLAT IS 1 1/4".
 2. MINIMUM SPACING BETWEEN 1-14 NPSM OPERATOR CENTERS IS 2 1/2" FOR THIS ENCLOSURE.
 3. MAXIMUM NUMBER OF OPERATORS IS 12.
 4. DIMENSION FROM CENTER LINE AND BACK OF MTS. LUG FOR CONDUIT.
 5. DIMENSION FROM CENTER LINE AND BACK OF MTS. LUG FOR CONDUIT.
 6. FOR MFG. ENCLOSURE USE 3/8 BOLT.

		MODIFIED XCE/XUF 101206 ENCLOSURE FOR	
DATE: 10/20/06 DRAWN BY: DDH CHECKED BY: DDH TOLERANCES: UNLESS OTHERWISE SPECIFIED: FRACTIONS: 1/16" DECIMALS: .001" DIMENSIONS: IN UNLESS OTHERWISE SPECIFIED	DATE: 10/20/06 DRAWN BY: DDH CHECKED BY: DDH TOLERANCES: UNLESS OTHERWISE SPECIFIED: FRACTIONS: 1/16" DECIMALS: .001" DIMENSIONS: IN UNLESS OTHERWISE SPECIFIED	DATE: 10/20/06 DRAWN BY: DDH CHECKED BY: DDH TOLERANCES: UNLESS OTHERWISE SPECIFIED: FRACTIONS: 1/16" DECIMALS: .001" DIMENSIONS: IN UNLESS OTHERWISE SPECIFIED	DATE: 10/20/06 DRAWN BY: DDH CHECKED BY: DDH TOLERANCES: UNLESS OTHERWISE SPECIFIED: FRACTIONS: 1/16" DECIMALS: .001" DIMENSIONS: IN UNLESS OTHERWISE SPECIFIED
SEE NOTES TUMBLAST XCE/XUF 101206	B-24-01 1-2.5 D	B-24-01 1-2.5 D	B-24-01 1-2.5 D
10F1	10F1	10F1	10F1