

XHD: Explosionproof/Flameproof Dual Pushbuttons

FEATURES

- Durable die-cast aluminum barrels
- Exposed aluminum components are anodized for superior corrosion and UV resistance
- Heavy-duty nylon buttons (one green, one red), pre-stamped "START" and "STOP"
- Long-lasting anodized aluminum heads (mushroom heads only)
- Designed for installation into ¾" NPSM entries

DESIGN OPTIONS

- Short and long-barrel (for enclosure covers thicker than ¾")
- Pad-lock provision (sold separately)
- Various contact block configurations
- Installed in Adalet enclosures with no installation charge

MATERIAL

- Barrels are 6061-T6 aluminum
- Caps are anodized 6061-T6 aluminum
- Buttons are nylon



XHDPB

FOR USE WITH SERIES BT CONTACT BLOCKS

Catalog #	Operator Description	Weight (lbs.)
XHDPB	Long Barrel - momentary*	½
XHDPBS	Short Barrel - momentary*	½
XHDPL	Padlock Device for Dual Pushbutton	½

*Two contacts in the BT contact block are actuated independently

LEGEND PLATES AT END OF SECTION

Certifications

Class I, Divisions 1 and 2, Groups B, C, and D

Class II, Divisions 1 and 2, Groups E, F, and G

Class III

NEMA Type 4, 7, and 9

NEMA Type 4X (with stainless steel cover bolt option)

UL 1203/CSA C22.2 No. 25 & 30

UL 1203/CSA C22.2 No. 25 & 30

UL 1203/CSA C22.2 No. 25 & 30

UL50

