## SINGLE SHUTOFF SINGLE SHUTOFF



SINGLE SHUTOFF SABERJET™

# TWO STREAMS ONE SHUTOFF!

**Solid Bore** 



- Solid Bore Reach and Penetration
- Low 50PSI Inlet Pressure
- High Volume Flow 3/4", 7/8", 15/16", or 1" Tips
- CAFS Capability



#### MULTIPLE APPLICATIONS:

- Interior
- Exterior
- High Rise
- CAFS
- Foam
- Direct Attack
- Indirect Attack
- Cooling
- Penetration
- Protection
- Ventilation
- SaberJet does them all.




2003 EDITION

Fog



- Operator Protection
- Ventilation
- Cooling & Extinguishing
- Foam Expansion
- Low Pressure Operation



newest in firefighting nozzle technology. With the penetration of a solid bore tip and the advantages of a fog pattern, the new Single Shutoff SaberJet has a unique three position handle and ball to give you smooth bore, fog or closed positions. The nozzle is capable of operating efficiently at pressures as low as 50 PSI for reduced firefighter fatigue, or up to 100 PSI for maximum flow. This versatile

nozzle is well suited for multiple applications. If you are looking for a truly multi-purpose nozzle, look no further... SaberJet is your answer.





#### **DUAL SHUTOFF SABERJET™ NOZZLE**

#### Solid Bore

Fog







- Dual Attack
- Penetration & Protection
- Draw In Fresh Air While Attacking
- Provides Cooling For Closer Attack



The Dual Shutoff SaberJet a truly multi-purpose nozzle with the penetration of a solid bore tip and the advantages of a fog pattern at the same time or independently. The nozzle is capable of operating efficiently at pressures as low as 50 PSI for reduced firefighter fatigue, or up to 100 PSI for maximum flow. Making it well suited for multiple applications.

### SINGLE & DUAL SABERJET™ DATA CHARTS

STYLE	SHUTOFF	INLET	TIP OPTIONS	FOG FLOW* GPM LPM		PISTOL GRIP	WEIGHT	LENGTH
1532	SINGLE	1½"	3/4", 7/8", 15/16", 1"	135	510	No	5 ¾ lbs.	111//8"
1533	SINGLE	1½"	3/4", 7/8", 15/16", 1"	135	510	Yes	6¼ lbs.	11½"
1535	SINGLE	2½"	3/4", 7/8", 15/16", 1"	135	510	No	6 lbs.	113/4"
1536	SINGLE	2½"	3/4", 7/8", 15/16", 1"	135	510	Yes	6½ lbs.	113/4"
1512	DUAL	1"	3/8", 1/2", 5/8"	60	230	Yes	5¾ lbs.	10½"
1513	DUAL	1"	3/8", 1/2", 5/8"	60	230	No	5 lbs.	10½"
1515	DUAL	1½"	3/8", 1/2", 5/8"	95	360	No	5 lbs.	10½"
1520	DUAL	1½"	3/8", 1/2", 5/8"	95	360	Yes	5 3/8 lbs.	10½"
1522	DUAL	1½"	34", 78", 15/16", 1"	135	510	No	5 3/4	11"
1523	DUAL	1½"	34", 78", 15/16", 1"	135	510	Yes	6 1/4	11"
1525	DUAL	2 ½"	3/4", 7/8", 15/16", 1"	135	510	No	6	11 1/8"
1526	DUAL	2 ½"	3/4", 7/8", 15/16", 1"	135	510	Yes	6 ½	11 5/8"
1527	DUAL	2½"	11/8"	135	510	No	6 lbs.	11 %"
1528	DUAL	2½"	1½"	135	510	Yes	6½ lbs.	11 1/8"

\*Fog Flow at 100 PSI (7 BAR)



In U.S./International Akron Brass Company PH: 330.264.5678 FAX: 330.264.2944

Available in Canada through: Akron Manufacturing Company PH: 519.773.8431 FAX: 519.773.3794

www.akronbrass.com

IN THE U.S. CALL 1.800.228.1161 | FAX 1.800.531.7335