

4 3 2 1

PART NO. SEE TABLE

# CUSTOMER DRAWING

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
A	新產品發行圖面	GARY	01/15/08

D  
C  
B  
A

D  
C  
B  
A

RECOMMENDED PCB LAYOUT

TABLE

007-01-00578	15 U" GOLD	LCP BLACK
PART NO.	PLATED	PLASTIC&COLOR

NOTE:

1.MATERIAL :  
 BASE : HIGH TEMPERATURE THERMOPLASTIC UL94V-0,  
 TERMINAL:COPPER ALLOY,THICKNESS = 0.30 mm  
 FORKLOCK:BRASS THICKNESS = 0.30 mm

2,PLATING:  
 CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE  
 SOLDER TAIL:150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE  
 GOLD SPECIFICATION:SEE TABLE

3.ELECTRONICAL SPECIFICATION:  
 CURRENT RATING: 1.5 AMPERE PER CONTACT  
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.  
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.  
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC.  
 OPERATING TEMPERATURE: -40°C~+85°C

-ã±1 A-A  
 φ 1:1

APPROVALS		DATE	PART NO. 007-01-00578			
DRAWN	GARY	01/15/08	TITLE: SATA 22PIN 加寬型兩排DIP			
CHECKED			SIZE	SCALE :	DRAWING NO.	REV.
APPROVALS			mm	1 : 1	000580	A
DO NOT SCALE DRAWING			ID NO.	XXXXXXXXXX	SHEET 1 OF 1	

NO	DESCRIPTION	QTY	UNIT
4	3		

4 3 2 1