



TOLERANCES: ±0.05

RECOMMENDED PCB LAYOUT

FPC/FFC T=0.30±0.05

**MATERIAL**  
 INSULATOR: GLASS-REINFORCED THERMOPLASTIC.  
 CONTACT: COPPER ALLOY.  
 PLATING: ALL TIN, LEAD FREE.

**ELECTRICAL**  
 CURRENT RATING: 0.5 AMP.  
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC MIN.  
 INSULATION RESISTANCE: 1000 MEGAOHMS MIN.  
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.

**ENVIRONMENTAL**  
 TEMPERATURE RANGE: -55°C TO 85°C.

**PART NO.**  
 BL118-XX S -0X  
 Series No. [XX] Packing Option [S]  
 No. Of Circuits [XX] STRAIGHT 180° (PARALLEL TYPE) (NORMAL TYPE)  
 2. Tube  
 4. Tape And Reel  
 5. Tape And Tube  
 6. Reel

**DIMENSION TABLE**

Circuits	Dimension				Circuits	Dimension			
	A	B	C	L		A	B	C	L
2	1.00	3.1	5	4	20	19.00	21.1	23	12
3	2.00	4.1	6		21	20.00	22.1	24	
4	3.00	5.1	7		22	21.00	23.1	25	
5	4.00	6.1	8		23	22.00	24.1	26	
6	5.00	7.1	9	8	24	23.00	25.1	27	
7	6.00	8.1	10		25	24.00	26.1	28	
8	7.00	9.1	11		26	25.00	27.1	29	
9	8.00	10.1	12		27	26.00	28.1	30	
10	9.00	11.1	13		28	27.00	29.1	31	
11	10.00	12.1	14		29	28.00	30.1	32	
12	11.00	13.1	15		30	29.00	31.1	33	
13	12.00	14.1	16		31	30.00	32.1	34	
14	13.00	15.1	17	12	32	31.00	33.1	35	
15	14.00	16.1	18		33	32.00	34.1	36	
16	15.00	17.1	19		34	33.00	35.1	37	
17	16.00	18.1	20		35	34.00	36.1	38	
18	17.00	19.1	21		36	35.00	37.1	39	
19	18.00	20.1	22						

RoHS Compliant				TOLERANCE		TITLE: FPC/FFC 1.0 FITCH NON ZIF TOP ENTRY DUAL CONTACT SMT TYPE - PARALLELED PCB LAYOUT	
E	Wilson	May.25.2006	LINEAR	ANGLES	PART NO. BL118-XX S		
D	Wilson	Sep.26.2005	X±0.40	X'±	DWG NO. BL118-XX S		
C	Wilson	Feb.28.2005	.X±0.30	.X'±	APPD: Jason	MAT'L:	
B	93038	Dec.30.2004	.XX±0.20	.XX'±	CHKD: Schumi	FINISH:	
REV	ECN NO.	NAME	DATE	.XXX±0.10	DRWN: Willson	Q'TY:	
						UNITS: MM	
						SCALE: 1 : 1	
						SHEET: 1 OF 1	
						REV: E	