

4

3

↓

2

1

PART NO. SEE TABLE

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
A	ease for Manufacture	Initial Rel	WITTY 05/07/08

CUSTOMER DRAWING

SECTION A-A
SCALE 1 : 1

TABLE

007-01-00657	15U"
007-01-00656	G/F
PART NO	PLATING

RECOMMEND PCB LAYOUT

NOTES:

1,MATERIAL:

HOUSING:HIGH TEMPERATURE THERMOPLASTIC,UL94 V-0,
COLOR:BLACK
CONTACT:COPPER ALLOY T=0.30mm

2,PLATING:

CONTACT:150U"MIN MISTY TIN PLATING ON SOLDER TAILS
50U"MIN NICKET UNDERPLATING OVER ALL GOLD SPECIFICATION:
a,G/F; b, 15u";

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING:1.5 AMPERE PER CONTACT
CONTACT RESISTANCE:30 MILLIOHMS MAX.
INSULATION RESISTANCE:1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING VOLTAGE:500 VAC.
OPERATING TEMPERATURE:-20°C~+85°C4.MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC OF THE
EUROPEAN PARLIAMANT AND OF THE COUNCIL OF 27 JANUARY
2003 ON THE RESTRICTION OF THE USE OF CERTAIN HAZARDOUS
SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT(ROHS)

DIMENSION ARE
MILLIMETERS
TOLERANCES ARE :
DECIMALS
.X ± 0.20
.XX ± 0.15
ANGLE:
X ± 1°

APPROVALS		DATE
DRAWN	WITTY	05/07/08
CHECKED		
APPROVALS		

TITLE: SATA 7P PLUG 180° SMT
A型 圓柱式全包有錯位(H=1.0)

SIZE	SCALE :	DRAWING NO.	REV.
mm	1 : 1	000619	A

ID NO. XXXXXXXXXX SHEET 1 OF 1

DESCRIPTION

Q'TY UNIT DO NOT SCALE DRAWING

4

3

↑

2

1