

4

3

2

1

PART NO. SEE TABLE1

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
D	CHANGE THE HOUSING	Jun.L	06/12/06
E	CHANGE TEMPERATURE RANGE AND PLATING	WITTY	07/24/06
F	修改圖面與實物相符	GARY	02/27/07
G	修改塑膠壁厚	GARY	09/19/07

**CUSTOMER
DRAWING**

TABLE 1

020-01-00149	15 U" GOLD	PA BLACK
020-01-00103	15 U" GOLD	LCP BLACK
PART NO.	PLATED	COLOR FOR THE PLASTIC

NOTE:

- MATERIAL :
HOUSING : High Temperature Thermoplastic ,
UL94V-0, COLOR : BLACK
TERMINAL(max): Copper Alloy, THICKNESS = 0.30 mm
TERMINAL(min): Copper Alloy, THICKNESS = 0.25 mm
FORKLOCK: Copper Alloy, THICKNESS = 0.30 mm
- PLATING:
CONTACT: GOLD OVER 50u" MIN NICKEL UNDERPLATE
SOLDER TAIL: 150u" MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE
GOLD SPECIFICATION: SEE TABLE
- ELECTRONICAL SPECIFICATION:
CURRENT RATING: 1.5 AMPERE PER CONTACT
CONTACT RESISTANCE: 30 MILLIOHMS MAX.
INSULATION RESISTANCE: 1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC.
OPERATING TEMPERATURE: -20°C ~ +85°C Δ
- MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27 JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT (ROHS)

RECOMMENDED PCB LAYOUT

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.20 .XX ± 0.15 ANGLE: X ± 3°	APPROVALS		DATE	PART NO. 020-01-00103/00149
	DRAWN	GARY	09/19/07	
	CHECKED			
	APPROVALS			
TITLE: SAS 29P Vertical DIP 3 platoun				REV. G
SIZE mm	SCALE : 1 : 1	DRAWING NO. 000237		
ID NO.	XXXXXXXXXX	SHEET 1 OF 1		

DESCRIPTION

Q'TY

UNIT

DO NOT SCALE DRAWING

4

3

2

1

NO