

## Dimensions and Part Names

		V9080iC
Power supply	Rated voltage	DC24V
	Permissible range of voltage	±10%
	Permissible momentary power failure	within 1ms
	Demand (maximum rating)	17W or less
Insulation resistance		DC500V 10MΩ or more
Physical environment	Ambient temperature	0 - 50 degree C <sup>*1</sup>
	Ambient humidity	85%RH or less (without dew condensation) <sup>*1</sup>
	Operation altitude	2,000 meters or lower
	Atmosphere	Not to be exposed to corrosive gas, or conductive dust
	Storage temperature	-10 to 60 degree C <sup>*1</sup>
	Storage temperature	85%RH or less (without dew condensation) <sup>*1</sup>
	Overvoltage category	Category II
Contamination level	Level 2	
Mechanical operating conditions	Resistance to oscillation	Complies with JIS B 3502 (IEC61131-2) Vibration frequency: 5 - 9Hz, pulsating with:3.5mm, 9 - 150Hz, Acceleration: 9.8m/s <sup>2</sup> (1G), X,Y,Z: 3 directions (10 times each)
	Resistance to shock	Complies with JIS B 3502 (IEC61131-2) Peak acceleration: 147m/s <sup>2</sup> (15G), X,Y,Z:3 directions, three times each (18 times in total)
Electric operating conditions	Resistance to noise	Noise voltage: 1,500Vp-p, pulse width: 1μs, pulse rise time: 1ns
	Resistance to static discharge	Complies with IEC61000-4-2, contact: 6kV, air: 8kV
Installation conditions	Grounding	Grounding resistance: Less than 100Ω, FG/SG separation
	Structure	Protect structure: Front panel: NEMA #250 TYPE 4X (indoor), TYPE 13 <sup>*2</sup> , equivalent to IP66 (when water-proof gasket is used.), Rear cover: Compatible with IP20, Form: Single unit, Installation method: Panel mounting
	Cooling system	Natural air cooling
	Dimensions W*H*D(mm)	235.0x180.0x48.9
	Dimensions W*H*D(mm)	220.5x165.5 (+0.5/-0)
Case color		Light gray
Material		PC

\*1: Keep wet bulb temperature under 39°C to avoid malfunction.

\*2: Available or complying after release.

## Performance Specifications

Screen memory (FROM)		64MB
Backup memory (SRAM)		800KB
Display	Display device	TFT color LCD
	Resolution	640x480
	Display size	8.4"
	Colors	16.7 million <sup>*3</sup>
	Backlight	LED
	Backlight life	70,000 hours
Touch switch	Type	Analog resistance film
Function switch	Quantity	8
External interface	D-Sub 9-pin (CN1)	RS-232C/ RS-422/485, Asynchronous type, Data length: 7,8 bits, Parity: even, odd, none, Stop bit: 1, 2 bits, Baud rate: 4800, 9600, 19200, 38400, 57600, 76800, 115200,187500 <sup>*4</sup> bps
	Modular 8-pin (MJ1/ MJ2)	RS-232C/ RS-422/485 (two-wire system), Asynchronous type, Data length: 7,8 bits, Parity: even, odd, none, Stop bit: 1, 2 bits, Baud rate: 4800, 9600, 19200, 38400, 57600, 76800, 115200 bps
	SD card	One card slot provided as standard
	Ethernet	1ch, Baud rate: 100Mbps, 10Mbps
	Wireless LAN	-
	USB	Type A, Type mini-B(Ver.2.0)
	Sound output	-
Clock	Backup period	5 years (Ambient temperature 25 degree C)
	Calendar accuracy	Gap ±90 sec. per month (Ambient temperature 25 degree C, when power is not supplied)
Standard	CE marking <sup>*5</sup>	EN61000-6-2, EN61000-6-4
	UL·cUL <sup>*5</sup>	UL508
	KC	Compliant
	Radio Act <sup>*5</sup>	-

\*3: For the display of pictures, 3D parts and videos only. Other parts are displayed in 65,536 colors.

\*4: Available only when connected with SIEMENS MPI/PPI.

\*5: DC type only.

Fuji Electric Corp. of America

50 Northfield Avenue, Edison, NJ 08837

Tel: 510.440.1060

Fax: 510.440.1063

For more information visit [www.americas.fujielectric.com](http://www.americas.fujielectric.com)