



ANACON
SYSTEMS

*EagleDrive*3™

Constant Torque

**200-240 Volts
1 Ph "In" / 3 Ph "Out"
1/2HP - 30.0HP**

**200-240 Volts
3 Ph "In" / 3 Ph "Out"
1/2HP - 60.0HP**




EagleDrive3™ is a family of Variable Frequency Drives designed to be cost-effective and easy-to-use controls for use with 3-phase induction motors. This Constant Torque series consists of thirty-two (32) ratings, fourteen (14) single-phase input ratings and eighteen (18) three-phase input ratings. Eagle Drive3 Constant Torque drives are well suited for conveyers, extruders, packaging machinery, machine tool and applications involving shock, overloads and high inertia loads. EagleDrive3 products use open loop voltage and frequency control to regulate the speed of the motor and are intended for general purpose application. The product is easy to install and simple to program.

- Single or Three Phase Input
- Push-Button Keypad
- "On-Board" Helpcard
- Bright LED Display
- Drive Efficiency: 95% +
- Speed Regulation: 1.0%
- c UL us & CE Approved
- OL Rating: 150% For 60 Second
- Minimum Full Load Torque: 3 Hz
- Selectable Inverter Switching Frequency
- Power Dip Ride Through
- Auto Restart Function
- Skip Frequency-Selectable
- Spinning Start-Selectable
- 3 Programmable Digital Inputs
- Powerful Performance & Features
- Analog Selectable Input
- Programmable Relay Input
- Auto Safe Shutdown
- Parameter Lock
- Protection Features
- Options: EMC Filters, EagleEye3 Hand-Held Wireless, EaglePort Remote Display & Programming, PI Control, RS232, RS485, etc.

For assistance call 888-456-3398 (Toll-Free)

EAGLEDRIVE³ DIMENSIONS

	Size 1	Size 2	Size 3	Size 4	Size 5	Size 6
Length mm / in	155/6.10"	260/10.24"	260/10.24"	520/20.47"	1045/41.14"	
Width mm / in	80/3.15"	100/3.98"	171/6.73"	340/13.39"	340/13.39"	
Depth mm / in	130/5.12"	175/6.89"	175/6.89"	220/8.66"	330/12.99"	
Weight kg / lb	1.1/2.42#	2.6/7.72#	5.3/11.66#	28/61.6#	68/149.60#	



CONSTANT TORQUE				
HP	Output Amps	kW	Part No.	Size
200-240V (1-Ph Input)				
0.5	2.3	0.37	ED-12005-US*	1**
0.75	3.1	0.55	ED-12007-US*	1**
1.0	4.3	0.75	ED-12010-US*	1**
1.5	5.8	1.1	ED-12015-US*	1**
2.0	7.0	1.5	ED-12020-US*	1**
2.0	7.0	1.5	ED-22020-US*	2
3.0	10.5	2.2	ED-22030-US*	2
5.0	19.5	3.7	ED-42100-01	4
7.5	23.0	5.5	ED-42150-01	4
10.0	30.5	7.5	ED-42200-01	4
15.0	44.5	11.0	ED-52300-01	5
20.0	55.0	15.0	ED-52400-01	5
25.0	75.0	18.5	ED-52500-01	5
30.0	90.0	22.5	ED-52600-01	5
200-240V (3-Ph Input)				
0.5	2.3	0.37	ED-12005-US*	1**
0.75	3.1	0.55	ED-12007-US*	1**
1.0	4.3	0.75	ED-12010-US*	1**
1.5	5.8	1.1	ED-12015-US*	1**
2.0	7.0	1.5	ED-12020-US*	1**
2.0	7.0	1.5	ED-22020-US*	2
3.0	10.5	2.2	ED-22030-US*	2
4.0	14.0	3.0	ED-32040-US	3
5.0	18.0	4.0	ED-32050-US	3
7.5	25.0	5.5	ED-32075-US	3
10.0	39.0	7.5	ED-42100-US	4
15.0	46.0	11.0	ED-42150-US	4
20.0	61.0	15.0	ED-42200-US	4
25.0	72.0	18.5	ED-42250-US	4
30.0	89.0	22.0	ED-52300-US	5
40.0	110.0	30.0	ED-52400-US	5
50.0	150.0	37.0	ED-52500-US	5
60.0	180.0	45.0	ED-52600-US	5

* 1 or 3-Phase Input

** Not suitable for fitting EagleBrake option

For assistance call 888-456-3398 (Toll-Free)

E-mail: info@anaconsystems.com Web Site: www.anaconsystems.com



Design & Sales Center: 9433 Bee Cave Road, Bldg. 1, Suite 140, Austin, TX 78733 - Tel: (512) 263-8668 – Fax (512) 263-8060
 Corporate Headquarters: 1043 Shoreline Boulevard, Suite 202, Mountain View, CA 94043 USA – Tel: (650) 934-3355 – Fax: (650) 934-3356

