### Model RD-120 SAMpack Isotope Identifier



## **FEATURES**

Sigma threshold triggering with auto correction.
(Allows high sensitivity during changes in background)

- < 9 lbs, Easily carried in serveral configurations</p>
- Low power consumption and Lithium Ion battery allows 24 hours operation

• Clandestine mode with or without earphones (e.g, vibration mode, color alert, real-time spectrum)

- Shock resitstant and water resistant
- Automated detector calibration
- Smart phone, ring tones, camera, etc.

## **APPLICATIONS**

- Emergency Response
- Law Enforcement
- Homeland Security
- Undercover Surveillance
- HAZMAT
- Industrial
- Medical
- Radiation Safety
- Passenger and Freight Monitoring
- Non-proliferation Enforcement
- Health Physics
- Environmental Waste Monitoring
- Unattended/Remote Monitoring



Berkeley Nucleonics Test, Measurement and Nuclear Instrumentation since 1963



# SAMpack

Standard Internal Detectors	3x3 Nal	Highest Sensitivity General Purpose Isotope Identification
	GM-Tube	High Gamma Count Rates
Internal Alternatives to Nal	1.5x1.5 LaBr	Highest Resolution Specialized Identification and Spectroscopy
	1.5x1.5 CeBr	Less Costly, High Resolution Identification and Spectroscopy
Optional Internal Detector	Neutron Option	Solid State Detector
Eectronics (MCA)	Digital Signal Processing	
	32 bit RISC, ARM Cortex	
	4096 Channels	
	150,000 CPS max	
Alarms	Automatic	Count Rate, Dose Rate, Health/Safety, Neutron Rate (optional),
	Adjustable Threshold	Fixed or Variable (up to 5 Sigma)
Data Output	Туре	1024 Channel Spectra, Alarm Conditions, Count Rates,
		Dose Rates, Channel Energy and Count, Time, Location
	Identification	Isotope, Classification, Confidence
	Energy Range	20 keV - 3.0 MeV
	Dose Rate Range	10 nR/hr - 10 R/hr
	Reachback	XML, per ANSI N42.42
Operational Modes	User, Administrator	Independently or Networked
Functions	Designed to meet or exceed requirements of ANSI N42.34 (2006)	
	Background, Dose, and Dose Rate	
	Search, Manual Capture, Automatic Capture,	
	Isotope ID	
Enclosure	IP65 Rated	Droppable to 1 m, Water Spray Resistant, Dustproof
	Dimensions	10" x 5" x 6"
	Weight	8 lbs max (w / Nal Detector)
	Operating Temperature	-20° C to 50° C
	Deployment	Handheld, 4 Steel Cleats for Shoulder Strap
	, ,	Detachable for Stand-off operation, Tripod Mountable
	25 ANSI, 7 SNM, 7 Medical, 7 Industrial, 4 NORM,	······································
Library	Customizable	
	Color Coded Classification Data	
	User enabled, On-screen Isotope Help Directory	
	Expandable to include 393 Isotopes from Kocher's	
	Radioactive Decay Data Table	
Smartphone Functions	Radioactive Decay Data Table Display	5" OLED Touch Screen
Smartphone Functions	Display	5" OLED Touch Screen Secure Mounting. Tilt-able and Rotatable
Smartphone Functions	Display Control	Secure Mounting, Tilt-able and Rotatable
Smartphone Functions	Display Control Event Alarms	Secure Mounting, Tilt-able and Rotatable Adjustable Speaker Volume, Headphones, Vibration, and Visual Display
Smartphone Functions	Display Control Event Alarms Location	Secure Mounting, Tilt-able and Rotatable Adjustable Speaker Volume, Headphones, Vibration, and Visual Display 3G GPS, Reported in Spectrum File
Smartphone Functions	Display Control Event Alarms Location Communication	Secure Mounting, Tilt-able and Rotatable Adjustable Speaker Volume, Headphones, Vibration, and Visual Display 3G GPS, Reported in Spectrum File Bluetooth, Wi-Fi, micro USB, and Cellular Netw ork (optional)
·	Display Control Event Alarms Location Communication Features	Secure Mounting, Tilt-able and Rotatable Adjustable Speaker Volume, Headphones, Vibration, and Visual Display 3G GPS, Reported in Spectrum File
File Memory	Display Control Event Alarms Location Communication Features 4.5 GB including Event Notes, Photos, Videos	Secure Mounting, Tilt-able and Rotatable Adjustable Speaker Volume, Headphones, Vibration, and Visual Display 3G GPS, Reported in Spectrum File Bluetooth, Wi-Fi, micro USB, and Cellular Netw ork (optional) Camera, Video and Voice Recording attached to Spectrum File
File Memory	Display Control Event Alarms Location Communication Features 4.5 GB including Event Notes, Photos, Videos Automatic Self-Calibration	Secure Mounting, Tilt-able and Rotatable Adjustable Speaker Volume, Headphones, Vibration, and Visual Display 3G GPS, Reported in Spectrum File Bluetooth, Wi-Fi, micro USB, and Cellular Netw ork (optional) Camera, Video and Voice Recording attached to Spectrum File
File Memory	Display Control Event Alarms Location Communication Features 4.5 GB including Event Notes, Photos, Videos Automatic Self-Calibration Automatic Self-Stabilization	Secure Mounting, Tilt-able and Rotatable Adjustable Speaker Volume, Headphones, Vibration, and Visual Display 3G GPS, Reported in Spectrum File Bluetooth, Wi-Fi, micro USB, and Cellular Netw ork (optional) Camera, Video and Voice Recording attached to Spectrum File
File Memory Calibration	Display Control Event Alarms Location Communication Features 4.5 GB including Event Notes, Photos, Videos Automatic Self-Calibration Automatic Self-Stabilization Manual Calibration	Secure Mounting, Tilt-able and Rotatable Adjustable Speaker Volume, Headphones, Vibration, and Visual Display 3G GPS, Reported in Spectrum File Bluetooth, Wi-Fi, micro USB, and Cellular Netw ork (optional) Camera, Video and Voice Recording attached to Spectrum File <sup>40</sup> K <sup>40</sup> K <sup>137</sup> Cs
Smartphone Functions File Memory Calibration Battery Details	Display Control Event Alarms Location Communication Features 4.5 GB including Event Notes, Photos, Videos Automatic Self-Calibration Automatic Self-Stabilization	Secure Mounting, Tilt-able and Rotatable Adjustable Speaker Volume, Headphones, Vibration, and Visual Display 3G GPS, Reported in Spectrum File Bluetooth, Wi-Fi, micro USB, and Cellular Netw ork (optional) Camera, Video and Voice Recording attached to Spectrum File

Berkeley Nucleonics Coporation - 2955 Kerner Blvd - San Rafael CA 94901 800-234-7858 or LiveChat @ www.berkeleynucleonics.com



# SAMpack

#### The Model RD-120-G SAMpack -- Backpack Radioisotope Device (BRD)

The Model RD-120-G is a remote controlled radiation detection and identification system which can be configured as a backpack, shoulder pack, stationary monitor or custom design. Clandestine operation is convenient with a smart phone or PDA Bluetooth controller. Operation is intuitive and automated with event monitoring in real time. ANSI standard reports and spectra are displayed on the smart device with the ability to manipulate the spectrum, review data and transmit all information to the users command center. The RD-120-G is designed to carry out various emergency response operations involving hazardous rad waste, orphaned sources, remediation activities and unobtrusively monitoring for WMD and RDD threats. The high sensitivity of large NaI detectors makes this system unique for many applications. GPS data, photos and note are also available which become part of the event log.





#### **Ordering Options:**

Model / P/N	Product Description
Model RD-120-G	SAMPack, Backpack Isotope Identifier
Model RD-120-GN	SAM Pack, Backpack Isotope Identifier with Neutron Detection
Model RD-120-LG	SAMPack, Backpack Isotope Identifier
Model RD-120-LGN	SAMPack, Backpack Isotope Identifier, Lanthanum, Neutron Detector
Model RD-120-CG	SAMPack, Backpack Isotope Identifier, Cerium
Model RD-120-CGN	SAMPack, Backpack Isotope Identifier, Cerium, Neutron Detector
Model RD-120-2CG	SAMPack, Backpack Isotope Identifier, 2.0 x 2.0 Cerium
Model RD-120-2CGN	SAMPack, Backpack Isotope Identifier, 2.0 x 2.0 Cerium, He3

Berkeley Nucleonics Coporation - 2955 Kerner Blvd - San Rafael CA 94901 800-234-7858 or LiveChat @ www.berkeleynucleonics.com