Length Cable Connector A **Connector B** Quote Jacket Type: PVC \Box Plenum \Box **Form PINOUT** A PIN# CONNECTION* B PIN# Fiber Cable Type **Copper Cable Type** ☐ Single-Mode Fiber ☐ Unshielded ☐ Multi-Mode 50/125µm Fiber ☐ Foil Shielded ☐ Multi-Mode 62.5/125µm Fiber ☐ Foil and Copper Braid Shielded ☐ Twisted Pair ☐ Simplex Fiber (2.9mm subunits) ☐ Category 3 Twisted Pair 2-Fiber Zipcord (2.9mm subunits) ☐ Category 5 Twisted Pair ☐ 1.6mm fan-out cable ☐ T1 Twisted Pair Specify # of fibers \Box Coax \Box 50 Ω \Box 75 Ω □ 2.9mm fan-out cable ☐ Multi-Conductor Coax Specify # of fibers_ □ Other:_ Other:_ Gender: Male \Box Gender: Male Female **Female Circle a Connector Type Circle a Connector Type** DB9 DB9 DB15 **DR15** DB25 DB25 **DB37 DB37** DB50 DB50 15-pin high density 15-pin high density 36-pin Centronics® V.35 (M/34) 36-pin Centronics® V.35 (M/34) RJ-11 4-position RJ11 6-position RJ-11 4-position RJ11 6-position RJ-45 8-position RJ45 10-Position RJ-45 8-position RJ45 10-Position DECTM MMJ DECTM MMJ M/50M/50Telco: 24-pin or 50-pin or 64-pin Telco: 24-pin or 50-pin or 64-pin 50-pin Berg: RS32 or SCSI 50-pin Berg: RS32 or SCSI Spade lugs-Length_ Spade lugs-Length_ SC Simplex SC Duplex SC Duplex FC SC Simplex FC ST II+ ST **FDDI** ST II+ ST FDDI LC Simplex LC Simplex LC Duplex LC Duplex MT/RJ MT/RJ Other:_ Other:_ **Circle Special Options Circle Special Options** Stub End Pins Only Stub End Pins Only Plastic Hood Metalized Plastic Hood Metalized Plastic Hood Plastic Hood Metal Hood Thumbscrews Metal Hood Thumbscrews Screwlocks: Male or Female Screwlocks: Male or Female 45-Degree Hood 90-Degree Hood 45-Degree Hood 90-Degree Hood -Cable Exit at Pin_ -Cable Exit at Pin Telco: Ears or Bail Latches Telco: Ears or Bail Latches 36-pin Centronics®: Ears or Bail Latches 36-pin Centronics®: Ears or Bail Latches Label: Label: Not Listed-Please Attach Specification Not Listed-Please Attach Specification **Circle Drain Wire Options Circle Drain Wire Options** Cut Drain Wire Attach to Hood Cut Drain Wire Attach to Hood Pin Drain by Itself to Pin #_ Pin Drain by Itself to Pin #_ Wrap Drain w/Conductor to Pin #_ Wrap Drain w/Conductor to Pin #_ Fax to: **Best-Tronics Mfg., Inc.** (708) 802-9676 *In the Connection box, enter wire color, draw brackets to indicate the twisted pairs, or leave blank for straight through Email to: sales@best-tronics.com