

Features:


1. Meet IEEE802.3 requirements.
2. Meet FCC class B approval.
3. SMD pick & place available.

Specifications:


Parts no.	Primary inductance (uH)min	Leakage inductance (uH)max	Primary Capacitance (pf)max	DCR (ohm) max	Rise Time (ns)max	Hi-Pot (vrms)	Turn Ratio	Package	Schematic
PT16-140A	140	0.3	12	0.30	5	1,500	1:1/1:1	A	1
PT16-140B	140	0.3	12	0.30	5	1,500	1:1/1:1	B	1
PT16-140SM	140	0.3	12	0.30	5	1,500	1:1/1:1	S	1
PT16-1402A	140	0.3	12	0.30	5	1,500	2:1/1:1	A	1
PT16-1402B	140	0.3	12	0.30	5	1,500	2:1/1:1	B	1
PT16-1402SM	140	0.3	12	0.30	5	1,500	2:1/1:1	S	1
PT16-2002A	200	0.3	20	0.60	5	1,500	1:1/1:1.414	A	1
PT16-2002B	200	0.3	20	0.60	5	1,500	1:1/1:1.414	B	1
PT16-2002SM	200	0.3	20	0.60	5	1,500	1:1/1:1.414	S	1
PT16-1402C	140	0.3	12	0.30	5	1,500	1CT:1CT	B	2
PT16-2004	200	0.3	12	0.30	5	1,500	1:1.414	B	3
PT20-1404C	140	0.3	12	0.30	5	1,500	1CT:1	C	4

Schematic:


1.



2.



3.



4.

