SAFETY DATA SHEET STENCIL CLEANER SCS/2

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME STENCIL CLEANER SCS/2

PRODUCT NO. 7052

SUPPLIER BLT Circuit Services Limited

Brome Industrial Estate

Brome, Eye Suffolk. IP23 7HN 01379 870870 01379 870970

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
1-METHOXY-2-PROPANOL	203-539-1	107-98-2	60-100%	R10
DIPROPYLENE GLYCOL MONOMETHYL ETHER	252-104-2	34590-94-8	10-30%	
N-METHYL-2-PYRROLIDONE	212-828-1	872-50-4	1-5%	Xi;R36/38

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Flammable.

CLASSIFICATION R10.

4 FIRST-AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention. NOTE! Keep affected person away from heat, sparks and flames!

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position. Rinse mouth thoroughly. Get medical attention.

SKIN CONTACT

Remove affected person from source of contamination. Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if irritation persists after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Alcohol resistant foam. Powder. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Ventilate closed spaces before entering them. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Do not scatter spilled material with more water than needed to fight the fire. Be aware of danger for fire to re-start. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

May explode in a fire. May develop highly toxic or corrosive fumes if heated. May travel considerable distance to source of ignition and flash back. Vapour explosion and poison hazard indoors, outdoors and in sewers.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Small quantities may be flushed to drains with plenty of water.

7 HANDLING AND STORAGE

STENCIL CLEANER SCS/2

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
1-METHOXY-2-PROPANOL	WEL	100 ppm(Sk)	375 mg/m3(Sk)	150 ppm(Sk)	560 mg/m3(Sk)
N-METHYL-2-PYRROLIDONE	WEL	25 ppm(Sk)	103 mg/m3(Sk)	75 ppm(Sk)	309 mg/m3(Sk)
DIPROPYLENE GLYCOL MONOMETHYL ETHER	WEL			150 ppm(Sk)	

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT





ENGINEERING MEASURES

Provide sufficient ventilation during operations which cause vapour formation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid

COLOUR Colourless

ODOUR Odour of alcohol

SOLUBILITY Soluble in water

RELATIVE DENSITY 0.93 @ 20 °c FLASH POINT (°C) 37 CC (Closed cup).

AUTO IGNITION TEMPERATURE (°C200 FLAMMABILITY LIMIT - LOWER(%) 1.7

FLAMMABILITY LIMIT - UPPER(%) 11.5

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions. SHELF LIFE 12 MONTHS

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

11 TOXICOLOGICAL INFORMATION

HEALTH WARNINGS

INHALATION. May cause irritation to the respiratory system. SKIN CONTACT. Prolonged or repeated contact leads to drying of skin. May cause skin irritation/eczema. EYE CONTACT. Irritating to eyes. INGESTION. May cause stomach pain or vomiting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Little danger to the environment.

STENCIL CLEANER SCS/2

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME FLAMMABLE LIQUID NOS contains 2-METHOXY-1- PROPANOL

UN NO. ROAD 1993 ADR CLASS NO. 3

ADR CLASS Class 3: Flammable liquids. ADR PACK GROUP 3(b) PACKAGING GROUP III

HAZARD No. (ADR) ADR LABEL NO. HAZCHEM CODE 2[S]E CEFIC TEC(R) NO. 544 **RID PACK GROUP** RID CLASS NO. 3 3(b) UN NO. SEA 1993 IMDG CLASS 3 IMDG PAGE NO. Ш 3244 IMDG PACK GR. **EMS** 3-06 **MFAG** 305 MARINE POLLUTANT No. UN NO. AIR 1993 **ICAO CLASS** AIR PACK GR. Ш

15 REGULATORY INFORMATION

RISK PHRASES

R10 Flammable.

SAFETY PHRASES

S51 Use only in well-ventilated areas.

S60 This material and its container must be disposed of as hazardous waste.

16 OTHER INFORMATION

REVISION DATE SEPTEMBER 2005

REV. NO./REPL. SDS GENERATED 4

SDS NO. SCS2/16/4

RISK PHRASES IN FULL

R10 Flammable.

R36/38 Irritating to eyes and skin.