

VX-023





RoHS Compliant



ExpressCard 1 Port RS422/485 1MBaud "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"

Sprainboxes.com Boost.Software Boost.Cord

Features

- 1 port RS422/485
- USB 2.0
- 128Byte Tx and 256Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



VX-023: ExpressCard 1 Port RS422/485 1MBaud

Description

ExpressCard providing one RS422/485 serial port. ExpressCard is 34mm wide and fits 34mm or 54mm slots. Data transfer rates up to 921,600 baud rates and the 128 byte deep transmit and 256 byte receive FIFOS coupled With 1Mbit/s line drivers deliver uncompromising performance on your laptop. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows XP, Server 2003, Vista, Server 2008, Windows 7 and Windows 8.

Low cost competitive range utilising USB technology. The most popular method of adding extra serial ports to your laptop.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support! Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 8 32 bit 64 bit Editions
- Windows 7 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.





ORDER Description ExpressCard 1 Port RS422/485 1MBaud

Code VX-023

+44(0) 151 220 2500 | sales@brainboxes.com | www.brainboxes.com

VX-023



ExpressCard 1 Port RS422/485 1MBaud

VX-023: Full Specification

Port	Ports	1 x RS422/485
Pin 1 TXD- Pin 2 TXD- Pin 3 RTS- Pin 4 RTS- Pin 6 RXD- Pin 7 RCTS Pin 6 Pin 6 Pin 7 CTS Pin 6 Pin 9	Connector	DB9 Connector - 9 Pin Male
	FIFO size	256 RX FIFO + 128 TX FIFO
	Operating Distance	RS422/485 Standard 4000 ft : 1200 metres
	Cable	No Cable; Integrated Connector
	Baud Rate	921,600
921,600 > > > > > baud	Data Bits	7 or 8
	Parity	Odd, Even, None, Mark or Space
	Stop Bits	1 or 2
	Flow Control	
	Tx/Rx Modes	Full Duplex, Half Duplex Autogating
nterface	OS Compatibility	Microsoft Windows 8 32 bit 64 bit Editions
USD A H		Microsoft Windows 7 32 bit 64 bit Editions Windows Vista 32 bit 64 bit Editions Mac OS X
	BUS	USB 2.0
Approvals	Other Approvals	AEO C-TPAT C-Tick Microsoft Certified Gold Partner WEEE RoHS METL EMC: CE TAA
	Microsoft Approvals	Windows 7 32 bit 64 bit Editions
		Windows Vista 32 bit 64 bit editions
		Windows XP 32 bit 64 bit editions
General	PCB Layers	4
	Power Consumption	80mA @ 3.3V
	Weight	0.03 kg
	Size	101l x 38w x 20h mm
ox Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	ExpressCard 1 Port RS422/485 1MBaud
		No Cable; Integrated Connector
roduct Support	Warranty	Lifetime (online registration required)
Elecktronos European Electronics Industry Awards WINNER Manufacturer of the Year Made in the	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Other Brainboxes Ranges: PCI Express | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial

+44(0) 151 220 2500 | sales@brainboxes.com | www.brainboxes.com