

Peppers Cable Glands Limited

Stanhope Road, Camberley, Surrey, GU15 3BT United Kingdom
 Telephone: +44 (0) 1276 64232 • Facsimile: +44 (0) 1276 691752
 Email: sales@peppers.co.uk • Website: www.cableglands.com



Cable Gland Accessories

A complete range of locknuts, earthtags, IP washers, serrated washers and shrouds.



LOCKNUTS		ISO Thread Dia	Minimum Thickness	Minimum A/F	Minimum A/C	Weight (Kgs/100)	NPT Thread Dia	Minimum Thickness	Minimum A/F	Minimum A/C
Locknuts are recommended for securing external entry threads into equipment. They are available in various materials such as brass, plated brass, stainless steel, aluminium and nylon.		M16 x 1.5	4.0	22.0	24.2	0.772	1/2"	3.2	27.0	29.7
		M20 x 1.5	4.0	24.0	26.4	0.683	3/4"	4.0	30.5	33.5
		M25 x 1.5	4.0	30.0	33.0	1.027	1"	5.0	38.1	41.9
		M32 x 1.5	4.0	40.0	44.0	2.020	1-1/4"	5.5	50.0	55.0
		M40 x 1.5	4.5	50.0	55.0	3.435	1-1/2"	6.0	60.0	66.0
		M50 x 1.5	5.0	65.0	71.5	6.997	2"	7.0	75.0	82.5
		M63 x 1.5	6.5	75.0	82.5	9.369	2-1/2"	9.0	90.0	99.0
		M75 x 1.5	7.0	90.0	99.0	14.871	3"	9.0	104.8	115.3
		M80 x 2	9.0	90.0	99.0	15.140	3-1/2"	10.0	114.3	125.7
		M85 x 2	9.0	104.8	115.3	27.518	4"	10.0	140.0	152.4
		M90 x 2	9.0	104.8	115.3	23.256	Sizes M110 to M130, PG7 to PG48 and BSPP / BSPT are available upon request			
		M100 x 2	9.0	114.3	125.7	25.256				
Note: Dimensions shown are only applicable to metallic locknuts		All dimensions in mm - Weights are based on metric versions								

EARTH TAGS		ISO Thread Dia	Minimum Thickness	Nominal Centres	Bolt Hole Dia	Weight (Kgs/100)	NPT Thread Dia	Minimum Thickness	Nominal Centres	Bolt Hole Dia
Earth tags are recommended for providing an earth bond connection for an entry component into the equipment. Earth tags are available in brass, plated brass, stainless steel and aluminium.		M16	1.5	31.8	6.9	0.746	1/2"	1.5	33.0	6.9
		M20	1.5	33.0	6.9	0.672	3/4"	1.5	36.5	6.9
		M25	1.5	36.5	6.9	0.797	1"	1.5	42.5	11.8
		M32	1.5	42.5	11.8	1.476	1-1/4"	1.5	45.4	13.5
		M40	1.5	45.4	13.5	2.089	1-1/2"	1.5	58.1	13.5
		M50	1.5	58.1	13.5	3.729	2"	1.5	66.8	13.5
		M63	1.5	66.8	13.5	4.898	2-1/2"	1.5	73.0	13.5
		M75	1.5	73.0	13.5	5.220	3"	1.5	90.0	13.5
		M80	1.5	73.0	13.5	4.647	3-1/2"	1.5	112.0	13.5
		M85	1.5	90.0	13.5	7.658	4"	1.5	120.0	13.5
		M90	1.5	90.0	13.5	6.669	Sizes M110 to M130, PG7 to PG48 and BSPP / BSPT are available upon request			
		M100	1.5	112.0	13.5	10.305				
Peppers Earth tags are compliant with the Category B requirements of EN 50262: 1999		All dimensions in mm - Weights are based on metric versions								

IP WASHERS		ISO Thread Dia	Thickness Nylon	Thickness Fibre	Outside Diameter	Weight (Kgs/100)	NPT Thread Dia	Thickness Nylon	Thickness Fibre	Outside Diameter
In order to maintain the integrity of an enclosure greater than IP54, washers are recommended to be installed at the gland entry interface.		M16	2.00	1.50	25.0	0.116	1/2"	2.0	1.50	30.0
		M20	2.00	1.50	29.4	0.164	3/4"	2.0	1.50	38.0
		M25	2.00	1.50	38.1	0.257	1"	2.0	1.50	46.3
		M32	2.00	1.50	42.5	0.341	1-1/4"	2.0	1.50	55.5
		M40	2.00	1.50	52.0	0.386	1-1/2"	2.0	1.50	60.0
		M50	2.00	1.50	65.0	0.594	2"	2.0	1.50	79.4
		M63	2.00	1.50	79.4	0.794	2-1/2"	2.0	1.50	90.5
		M75	2.00	1.50	90.5	0.868	3"	2.0	1.50	114.3
		M80	2.00	1.50	104.8	0.839	3-1/2"	2.0	1.50	114.3
		M85	2.00	1.50	104.8	0.698	4"	2.0	1.50	146.0
		M90	2.00	1.50	114.3	0.913	Sizes M110 to M130, PG7 to PG48 and BSPP / BSPT are available upon request			
		M100	2.00	1.50	114.3	0.512				
Colour Fibre Metric = Red NPT = Red Nylon Metric = Red NPT = White PTFE Metric = White NPT = White		All dimensions in mm - Weights are based on metric versions								

SERRATED WASHERS		ISO Thread Dia	Minimum Thickness	Outside Diameter	Weight (Kgs/100)	NPT Thread Dia	Minimum Thickness	Outside Diameter		
Serrated or "shake proof" washers act as an anti-vibration devices to prevent the cable gland, or other cable entry device and locknut arrangement from loosening. It can also be used as an earth enhancing device on painted enclosures. They are only available in Stainless Steel.		M16	1.5	25.5	0.262	1/2"	1.5	35.4		
		M20	1.5	32.4	0.560	3/4"	1.5	43.4		
		M25	1.5	37.4	0.675	1"	1.5	52.0		
		M32	1.5	48.0	1.042	1-1/4"	1.5	59.5		
		M40	1.5	60.0	1.730	1-1/2"	1.5	71.0		
		M50	1.5	71.0	2.154	2"	1.5	87.0		
		M63	1.5	87.0	3.259	2-1/2"	1.5	102.0		
		M75	1.5	102.0	4.189	3"	1.5	125.0		
		M80	1.5	120.0	6.880	3-1/2"	1.5	140.0		
		M85	1.5	125.0	6.550	4"	1.5	155.0		
		M90	1.5	125.0	6.233	Sizes M110 to M130 are available upon request				
		M100	1.5	140.0	7.985					
Order Code Example Stainless Steel ACSSW/M20		All dimensions in mm - Weights are based on metric versions								

SHROUDS		Order Code	Example	Temperature
Peppers manufacture a range of shrouds in various materials to complement our complete range of glands. Materials available are Polyvinylchloride (PVC), Polychloroprene (PCP) & Low Smoke Halogen Free Silicone (LSOH). Please note that the shrouds are manufactured to fit our glands and will not necessarily fit other manufacturer's products. The shroud sizes are detailed on each of the product pages.		PVC	ACSPVC/L24	-25°C to +70°C
		PCP	ACSPCP/L24	-30°C to +100°C
		LSOH	ACSSIO/L24	-60°C to +200°C
Please note that glands with larger than standard entry threads will require a larger shroud in order to fit over the gland hexagon body section				