

CONTROL CONCEPTS CONNECT

GATEWAY MODULE

DESCRIPTION

Control Concepts' Connect is a fieldbus gateway module that can link up to 10 MicroFUSION units using CCI Link, a dedicated, real-time, deterministic digital bus.

The Connect module reduces per-point cost for digital system connectivity and gives full access to monitor parameters that are only available over a dedicated digital bus.

FEATURES

- Controls up to 10 Zones
- Protocols:
 - EtherCAT
 - EtherNet/IP
 - Modbus TCP
 - PROFINET (maximum 6 zones)
 - PROFIBUS (maximum 6 zones)
- Data Logger
 - Battery-backed real time clock
 - · Removable SD Card
 - Records data in 100 ms to 1 minute intervals
- Micro USB port for easy setup
- Panel mount or Din-Rail mount





gateway. Maximum power of 480 KW

DIMENSIONS

Dimensions: Inches [mm]





SPECIFICATIONS

ENVIRONMENTAL	VIRONMENTAL	
Power Consumption	200 mA Amps at 24 Vdc - Powered from CCI Link	
Surrounding Air Operating Temperature	32°F [0°C] - 122°F [50°C]	
Humidity	20% to 90% RH Non-Condensing	
Rated Operating Altitude	Up to 6000 ft [1829m]	
Contaminates	ROHS Compliant, CE Pollution Degree 2	
Storage Temperature	- 4 to 176°F [- 20 to 80°C]	
Heatsink Options	Panel Mount or Din Rail Mountable	

	SD Card		
	Capacity	16 GB Included. Maximum compatible storage: 64 GB	
	Logging Channels	Up to 10 devices	
	Logging Intervals	100 ms to 1 minute	

DIGITAL BUS PERFORMANCE	
Command Latency	≤ 100 ms
Monitor Latency	≤ 100 ms
Update Period	≤ 100 ms

MODEL NUMBERS

Communication -

L = Data Logger Only E = Modbus TCP I = EtherNet/IP N = PROFINET

C = EtherCAT

Consult factory for additional fieldbus interfaces

Nodes

03 - Communicate with up to three nodes

06 - Communicate with up to six nodes

10 - Communicate with up to ten nodes

Configuration Data -

Supplied by Control Concepts. 0000 default if not supplied by CCI.

CONTACT/ORDERING INFORMATION

TEL: (952) 474-6200 | (800) 765-2799 FAX: (952) 474-6070 | www.ccipower.com 18760 Lake Drive East, Chanhassen, MN 55317, USA

