

UHF Narrow Band Multi Channel Transceiver

STD-302S 429MHz

The UHF FM narrow band semi-duplex radio module STD-302S 429MHz is suitable for industrial remote control application and telemetry application operated in 429MHz ISM band. SAW filter and narrow band technique provides reliable data communication in industrial applications where interference rejection and practical distance range is required. Suitable for feedback systems.

Features

- 10mW RF power, 3.0V
- Programmable RF channel
- Receiver sensitivity -120 dBm
- Excellent vibration and shock resistance / Mechanical durability
- FM narrow band
- 434 MHz also available

Applications

- Industrial remote control system
- Telemetry system
- Data transmission



General

| Parameter | Specification |
|-------------------------|--|
| Communication form | Half duplex |
| Frequency | 429.25 to 429.7375 MHz |
| Channel step | 12.5 kHz Channel programmable (PLL IC:Fujitsu MB15E03) |
| Frequency stability | +/- 4 ppm (-20 to + 60 degree C) |
| Data rate | 4,800 bps max (Pulse width min. 200 us, max 20ms) |
| PLL reference frequency | 21.25 MHz (TCXO) |
| PLL response | 30 ms typ. (from PLL setting to LD out) |
| Modulation | FSK |
| Supply voltage | 3.0 to 5.5 V |
| Supply current | 44 mA typ (TX) 26 mA typ (RX) |
| Operating temp. range | -20 to + 60 degree C (Storage : -30 to + 75 degree C) |
| TX/RX switching time | 15 ms typ. (DI vs valid DO at the same frequency) |
| Dimension | 30 X 50 X 9 mm |
| Weight | 25g |

Transmitter part

| Parameter | Specification |
|-------------------|----------------------------|
| Transmitter type | PLL synthesizer |
| RF output power | 10 mW at 50 ohm |
| Deviation | +/- 2.0 kHz (PN9, 4800bps) |
| DI input level | L = GND, H = 3 V to Vcc |
| Residual FM noise | 0.17 kHz |
| Spurious emission | -27 dBm max. |
| Adjacent CH power | -40 dBm (PN9 4800 bps) |

Receiver part

| Parameter | Specification |
|------------------------------|---|
| Receiver type | Double superheterodyne |
| IF | 21.7 MHz (1st), 450 kHz (2nd) |
| Maximum input level | 10 dBm |
| Receiver sensitivity | -120 dBm (12 dB SINAD) -120 dBm (BER 1%) -115 dBm (0 error / 2556 bits) |
| Spurious response rejection | 70 dB (1st Mix), 55 dB (2nd Mix) |
| Adjacent channel selectivity | 50 dB (+/- 12.5 kHz) |
| Intermodulation | 50 dB (f - 200 kHz + f - 100 kHz) |
| Spurious radiation | -54 dBm max. |
| DO output level | L = GND, H = 2.8 V |

Specifications are subject to change without prior notice