

32ch

UHF Narrow Band Multi Channel Transmitter/Receiver CDP-TX-02E-R, CDP-RX-02E-R 457 MHz

The unique and compact CDP - TX/RX - 02E - R 457 MHz is a frequency selectable radio data module.

Both CDP-TX-02E-R (transmitter) and CDP-RX-02E-R (receiver) are equipped with a frequency synthesizer system including microprocessor. 32 RF channels are selectable using an onboard 4-bit switch. Its small size, low voltage operation, and frequency selectability of CDP-02E-R make it ideal for various applications in sites where many radio transmitters are operated.

Features

- 32 frequency synthesized RF channels
- 1 mW / 10 mW selectable
- Low voltage operation
- High sensitivity receiver
- FM narrow band modulation
- FCC Part 90 (Transmitter) & Part 15 (receiver) compliant

Applications

- Mobile / Handheld Portable device defined by FCC
- Industrial remote control
- Factory automation M2M
- Security systems
- Alarms
- Telemetry systems



General

Parameter	Specification (All ratings at 25 degree C unless otherwise noted)
Communication form	One way
Oscillation system	PLL controlled VCO
Modulation / Demodulation	FSK
Frequency range	457.5 MHz to 457.8875 MHz
Number of RF channels	32 ch
Channel step	25 kHz
Channel selection method	4 bit switch
Frequency stability	+/- 4.0 ppm or less (-20 to +60 degree C)
Data rate	2400 bps max. (Min. pulse width 410 us, Max. pulse width 20ms)
Operating temp. range	-20 to +60 degree C (No dew condensation)

CDP-TX-02E-R (Transmitter)

Parameter	Specification
Transmitter type	PLL synthesizer
RF output power	10 mW / 1 mW selectable
Transmitter start up time	50 ms (from power on)
Data input	Digital (L = GND H = 3.0 to 5.5 V)
Deviation	+/- 2.1 kHz (PN9 2400 bps LPF 20 kHz)
Spurious emission	30 dBc or more
Adjacent channel power	40 dBc or more
Supply voltage	3.0 to 12 V DC
Supply current	43 mA typ. at 3V/10 mW 33 mA typ. at 3V/1 mW
Dimensions	36 X 26 X 10 mm (excluding protrusion)
Weight	14 g (without antenna)

CDP-RX-02E-R (Receiver)

Parameter	Specification
Receiver type	Double Superheterodyne PLL synthesizer
Sensitivity	- 120 dBm typ. (at AF / 12 dB/SINAD at CCITT filter fm=1 kHz) - 120 dBm typ. (at DO / BER 1% at 4800 bps PN9) - 116 dBm typ. (at DO / BER 0 error / 2556 bits at 4800 bps PN9)
Adjacent CH selectivity	60 dB (+/- 25 kHz)
Blocking	84 dB (All)
Spurious radiation	-57 dBm
Data output	Digital (L = GND H = Vcc)
Supply Voltage	3.0 to 12 V DC
Supply current	30 mA typ. at 3 V
Dimensions	50 X 30 X 9 mm (excluding protrusion)
Weight	20 g

Specifications are subject to change without prior notice