



SPECIFICATIONS

Current Rating: 1 Amp
 Contact Material: Brass or Phosphor Bronze
 Insulator Material: UL94V-0
 Insulation Resistance: 1000MΩ Min.
 Withstanding: 500 VAC
 Operating Temp: -40°C ~ +85°C

Dimensions				
Contact	A	B	C	D
06	12.18	05.08	13.10	1.90
08	14.72	07.62	13.10	1.90
10	17.26	10.16	13.35	3.60
12	19.80	12.70	13.35	3.60
14	22.34	15.24	13.35	3.60
16	24.88	17.78	13.35	3.60
18	27.42	20.32	13.55	3.60
20	29.96	22.86	13.35	3.60
24	35.04	27.94	13.35	3.60
26	37.58	30.48	13.35	3.60
30	42.66	35.56	13.35	3.60
34	47.74	40.64	13.35	3.60
36	50.43	43.18	13.35	3.60
40	55.36	48.26	13.35	3.60
44	60.64	53.34	13.55	3.60
50	68.06	60.96	13.35	3.60

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	01/08/05
				Checked	Lizzy	01/08/05
				Drawn	Tina	01/08/05
		0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'		
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **AFC-113B0-16-P-GD**

Description: Flat Cable for CBL-12236-A