

ADAPTER POWER SUPPLY

AC-DC 150W



CT-1F3DB24

Features:

- Universal AC Input 99~264Vac
- Low ripple noise
- No minimum load requirement
- 100% burn in test
- 1 year warranty
- UL,cUL,GS,CB,CE,FCC standard
- Meet EPS 2.0 LEVEL V



Dimension:




Model No.	Output		Additional Safety
CT-1F3DB24	24V	6.25A	

Specification:

REV.01 2011.3.2



Input	Voltage	AC 99V~264V Universal full range
	Frequency	47-63Hz
	Current	2.0A MAX
	Leakage Current	< 3.5mA
Others	Start up time	<3000mS @ Minimum AC input
	Rise time	<50mS
	Hold up time	>10mS @ 230Vac/50Hz input
	Cooling	Natural Cooling
Environment	Temperature	Operating: 0~40℃;Storage: -10~+75℃
	Humidity	Operating: 20%~85%;Storage: 10%~95%(Non Conversing)
M.T.B.F	50k Hours	
Safety	UL 60950-1,CSA C22.2 No.60950-1/IEC 60950-1	
EMC	EMI	FCC CFR 47 PART 15 , EN55022 , EN61000-3
	EMS	EN55024(EN61204-3) EN61000-4



ADAPTER POWER SUPPLY

AC-DC 150W


CT-1F3NB24

Features:

- Universal AC Input 99~264Vac
- Low ripple noise
- No minimum load requirement
- 100% burn in test
- 1 year warranty
- UL,cUL,GS,CB,CE,FCC standard
- Meet EPS 2.0 LEVEL V



Dimension:



Model No.	Output		Additional Safety
CT-1F3DN24	24V	6.25A	

Specification:

REV.01 2011.3.2



Input	Voltage	AC 99V~264V Universal full range
	Frequency	47-63Hz
	Current	2.0A MAX
	Leakage Current	< 3.5mA
Others	Start up time	<3000mS @ Minimum AC input
	Rise time	<50mS
	Hold up time	>10mS @ 230Vac/50Hz input
	Cooling	Natural Cooling
Environment	Temperature	Operating: 0~40°C;Storage: -10~+75°C
	Humidity	Operating: 20%~85%;Storage: 10%~95%(Non Converting)
M.T.B.F	50k Hours	
Safety	UL 60950-1,CSA C22.2 No.60950-1/EN60950-1/IEC 60950-1	
EMC	EMI	FCC CFR 47 PART 15 , EN55022 , EN61000-3
	EMS	EN55024(EN61204-3) EN61000-4

