



N320E-G2-CR

PCI Express  
Gen 2 interface

## Best Price/Performance 10GbE Server Adapter

TCP/IP • Storage • Computing Applications

### Highlights

- PCI Express Gen 2 host bus interface
- Line-rate 10Gbps full-duplex performance
- Extensive stateless offload capability
- Efficient DMA software architecture to boost performance
- Large Receive Offload (LRO)
- Large Send Offload (LSO)
- Checksum offload for TCP, UDP IP and Ethernet
- Minimized interrupts for device management
- Minimized programmed I/O read access
- Turn-key drivers for major server operating systems

### Applications


#### Link Consolidation

- Upgrade a server's multiple Gigabit Ethernet connections to improve bandwidth and simplify cabling

#### Server Consolidation

- Replace a group of servers with fewer higher-performance systems and higher bandwidth to reduce rack congestion, cabling, power consumption, and simplify maintenance

CHELSIO'S N320E Server Adapter is a dual-port 10 Gigabit Ethernet adapter with PCI Express host bus interface for servers and storage systems. The cost-effective N320E provides higher bandwidth for end nodes for organizations using 10 Gigabit Ethernet in the data center with advanced stateless offload. The N320E represents the third generation of Chelsio's server adapters. Easy to deploy, it comes complete with turn-key drivers for major server operating systems.



Chelsio's 10 Gigabit Ethernet adapters have been subjected to thousands of hours of compatibility testing and over two years of stress testing by various OEM test suites, with different operating systems. The robust N320E delivers the most reliable performance and best value for 10GbE connectivity in the industry.

The adapter's two ports and IEEE 802.3ad link aggregation/failover features are ideal for critical network applications that require redundancy and high-availability capabilities.

### Benefits

By using Chelsio's N320E, enterprises can cost-effectively connect servers and storage systems directly to the 10GbE backbone switching infrastructure over multi-mode or single-mode fiber.

As an upgrade or an alternative to aggregated Gigabit Ethernet links, 10GbE boosts connection bandwidth and simplifies cabling, installation, and maintenance. The N320E also provides additional bandwidth needed to consolidate server functions on fewer, more powerful systems – simplifying management and reducing costs for servers, rackspace, power consumption, and maintenance.

Applications with large data sets benefit from a high-speed distributed platform, including video rendering and distribution, data visualization such as remote medical imaging and climatic modeling, and bioinformatics applications such as DNA sequencing.

## Fully Featured Server Adapter

The dual-port N320E offers best-of-class performance and features, including IP/UDP/TCP checksum and large send offload, rate control and QoS, virtualization, and rule-based traffic steering and filtering.

## Third-Generation Protocol Offload Engine

The N320E employs Chelsio's unique third-generation Terminator 3 ASIC, a high-performance, programmable protocol processor. Terminator 3 processes all connections in a single datapath to deliver line-rate 10Gbps performance with one connection, up to thousands of connections. In contrast, competitive multi-RISC offload engines, which rely on having enough connections to distribute their processing among parallel processors to achieve full performance, are ultimately limited by the performance of each processor.

## Robust, Proven Solution

Subjected to thousands of hours of compatibility testing, over two years of stress testing by several OEM test suites and production deployments in servers, storage systems and cluster computing, Chelsio's robust, stable protocol offload technology delivers proven performance in a wide range of environments. The N320E is generations ahead of competing products.

## Software Drivers

Chelsio offers a full suite of protocol software and drivers with the N320E adapter. See [www.chelsio.com/support](http://www.chelsio.com/support) for latest info.

## Product Models

**Model:** N320E-G2-CR

**Physical interface:** 10GBASE-SR or LR<sup>†</sup>

**Distance:** 300m or 10km

**Connector:** LC Duplex

**Media:** MMF or SMF

<sup>†</sup>SFP+ optics sold separately. Only Chelsio-supplied modules may be used:

- SM10G-SR 10G short-reach SFP+ optic module
- SM10G-LR 10G long-reach SFP+ optic module
- SRCABLE3M Fiber optic cable, 10GBASE-SR, 3-meter
- LRCABLE3M Fiber optic cable, 10GBASE-LR, 3-meter
- TAPCABLE1M Twin-ax passive cable, 1-meter
- TAPCABLE3M Twin-ax passive cable, 3-meter
- TAPCABLE5M Twin-ax passive cable, 5-meter

## Specifications

### Host Interface

- PCI Express Gen 2 x8, x4, x1
- MSI-X, MSI and support for legacy pin interrupts

### Network Interfaces

- 10GBASE-SR short-reach optics (850nm)
- 10GBASE-LR long-reach optics (1310nm)
- Direct Attach Twin-ax copper

### Ethernet

- IEEE 802.3ae (10GbE)
- IEEE 802.1p Priority and 802.1Q VLAN tagging
- IEEE 802.3x flow control
- IEEE 802.3ad link aggregation
- Ether II and 802.3 encapsulated frames
- Multiple MAC addresses per interface
- Jumbo Frames up to 9.6Kbytes

### Stateless Offloads

- TCP checksum offload for IPv4 & IPv6
- TCP Segmentation Offload (TSO) for IPv4 & IPv6
- Large Receive Offload (LRO) for IPv4 & IPv6
- Large Send Offload (LSO) for IPv4 & IPv6
- UDP checksum offload for IPv4 & IPv6
- Receive Side Scaling and packet steering
- Attack protection

### Physical and Environmental

- Dimensions without bracket: 6.7 in. x 4.3 in. or 17.0 cm x 10.9 cm
- Operating Temp: 0 to 55°C or 32 to 131°F
- Operating Humidity: 5 to 95%
- Airflow: 200 lf/m
- Typical power consumption: <25W

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH CHELSIO PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN CHELSIO'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, CHELSIO ASSUMES NO LIABILITY WHATSOEVER, AND CHELSIO DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF CHELSIO PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. CHELSIO PRODUCTS ARE NOT INTENDED FOR USE IN MEDICAL, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS. CHELSIO MAY MAKE CHANGES TO SPECIFICATIONS AND PRODUCT DESCRIPTIONS AT ANY TIME, WITHOUT NOTICE.