

CHERRY JK-0720EU



Models may vary from the image shown

Compact Keyboard for Professional Use with Backlighting

CHERRY JK-0720 is advanced CHERRY technology in a modern, flat compact design with soft, quiet keys, as well as 3-stage adjustable white backlighting.

Key Benefits

- Flat and compact professional keyboard with quiet, short stroke keys
- 3-stage LED backlighting for key symbols (white)
- Scissor technology: Up to 10 million key actuations
- Adjustable cable routing from the casing (left/center/right)
- Plug & Play via USB connection
- Two-tone key labeling

Technical Data:

Housing Color: Black

Key Color: Black

Weight (product):

Approx. 345 g / .76 lbs

Total Weight (with packaging):

Approx. 488 g / 1.07 lbs.

Cable Length:

Approx. 1.80 m / Approx. 5.91 ft.

Current Consumption:

Max. 200 mA

Operating Temperature:

0° C to 50° C / 32° F to 122° F





Storage Temperature:

-20° C to 60° C / -4° F to 140° F

Interface:

USB

Product Approvals:

C-Tick	
CE	
FCC	
UL	

System Requirements:

USB connection

Delivery Volume:

CHERRY JK-0720

Operating instructions in hard copy

Dimensions (product):

Approx. 305 x 146 x 15 mm

Approx. 12.00" x 5.74" x .59"

Packaging Dimensions :

Approx. 350 x 146 x 25 mm

Approx. 13.7" x 5.7" x .98"

Reliability:

MTBF (90) > 80,000 hours

Keyboard:

- Key technology: SX (scissor switch)
- Service life, standard key: > 10 million key operations
- Inscription technology: Laser
- Inscription layout: Standard
- Number of Keys: 88

Packaging Unit:

Number of products in the master package: 20

Number of master packages per pallet: 24

Warranty:

2 years



Model:

Service Design	Product Name	Order Number	EAN Code
Light Use	CHERRY KC 4020	JK-0720EU	4025112078156

(Possible country/layout versions, others available on request)

Cherry Americas, LLC
11200 88th Avenue
Pleasant Prairie, WI 53158
USA
Phone: 262.942.6508
Internet: www.cherryamericas.com
E-Mail: keyboardsupport@cherryamericas.com

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

Rev Date: January 17, 2017