



OCXO-3627

Frequency Range (频率范围)	10~60 MHz
Typical Frequency (常用频率点)	10, 13 14,7456, 16.384, 19,2 20, 25, 26, 32,768, 40, 49.152 MHz
Temperature Range (°C) Operating (工作温度范围)	From -40 to +80 A1: -10 ~ +60 A2: -20 ~ +70 A3: -30 ~ +75 A4: -40 ~ +80
Storage (储藏温度范围)	-55 to +125
Supply Voltage (电源电压)	5V, 12V
Power Consumption (功耗) During Warm-up (启动) At steady State (稳定) @0°C @25°C	≤3.2W ≤1.2W ≤0.9W
Frequency Stability Vs (频率稳定度 VS) Temperature (温度) Shot Term Stability (秒稳定度) Long Term Stability (日稳定度)	≤±10 to +/- 100 ppb 2×10 ⁻¹⁰ @1S, 0.5×10 ⁻¹⁰ @1S ≤±0.1 to +/- 1ppb (typical) per day
Output (输出负载)	HCMOS, Load: 15pF(typical) Sine, Load: >0 to 7 dBm/50Ω
Reference Output (输出幅度)	4.5V or 5.0 V
Control Input (输入控制) Voltage (电压) Impedance (阻抗) Transfer Slope () Tuning Range (调节范围)	0-5V or any other option 50k to 200K Ω Positive ±0.45~2.5ppm
Phase Noise (相位噪声)	Case by Case (一单一议)
Package (外形封装) Size (尺寸)	HMD 36×27×14mm, 36×27×19 mm

