



E1X

**E1X Double Seal Industrial Cable Gland
For Braid & Steel Tape Armoured Cables**

- Metal-to-metal armour clamping
- Direct & remote installation
- Permanently crimped, low impedance earth termination
- Secure against self-loosening
- Displacement type inner seal
- Controlled outer 'load retention' seal
- Unique OSTG prevents overtightening
- Designed to prevent Coldflow
- Deluge protection option
- -60°C to +130°C
- EMC tested



† Grooved Cone (X) is predominantly used for Wire Braid (e.g. GSWB, TCWB), Steel Tape Armour (STA, DSTA) and Aluminium Strip Armour (ASA) but is also suitable for single Wire Armour (SWA), Aluminium Wire Armour (AWA) and Pliable Wire Armour (PWA) if the range is outside that of the Stepped Cone (W).

Note: Grooved Cone (X) dimensions shown in the Cable Gland Selection Table below are for a double wire strand of braid armour cables. Tapes can also be doubled over. For cables that have only a single layer of armour such as SWA the clamping range should be used as shown in the table below.

If Tape Armour is to be used please contact CMP for advice.

TECHNICAL DATA	
Design Specification	BS 6121:Part 1:1989, IEC 62444, EN 62444
Mechanical Classifications*	Impact = Level 8, Retention = Class D
Enclosure Protection	IK10 to IEC 62262 (20 joules) Brass & Stainless Steel only
Electrical Classifications*	Category B (Category A when used with braid, tape or pliable wire armour cables)
GOST R Certificate No.	POCC GB. ГБ05.H00187
GOST K Certificate No.	KZ 7500361.01.01.25266
RoK Permit For Use Number	19-02-UL-1957
Marine Approvals	LRS: 01/00171 (E1), ABS: 01-LD234401/2-PDA
Ingress Protection Rating	IP66 as standard (IP67, IP68 available upon request)**
Cable Gland Material	Brass, Electroless Nickel Plated Brass, Aluminium
Seal Material	CMP Thermoset Rubber
Cable Type	Wire Braid Armour, Screened Flexible (EMC) Wire Braid (e.g. CY / SY), Pliable Wire Armour (PWA), Steel Tape Armour (STA), Aluminium Strip Armour (e.g. ASA)
Armour Clamping	Detachable Armour Cone & AnyWay Universal Clamping Ring
Sealing Technique	CMP Inner Displacement Seal & Unique CMP 'LRS'™ Outer Load Retention Seal
Sealing Area(s)	Cable Inner Bedding & Outer Cable Sheath

Note : * Mechanical & Electrical Classifications applied as per IEC 62444 & EN 62444
Note : ** Refer to page 7 or www.cmp-products.com for further information on Ingress Protection Ratings

Cable Gland Selection Table
Refer to illustration at the top of the page

Cable Gland Size	Available Entry Threads "C" (Alternate Metric Thread Lengths Available)					Cable Bedding Diameter "A"		Overall Cable Diameter "B"		Armour Range † Grooved Cone (X)		Across Flats "D"		Across Corners "D"		Protrusion Length "F"	Combined Ordering Reference (*Brass Metric)			Shroud	Cable Gland Weight (Kgs)
	Metric	Standard		Option		Min	Max	Min	Max	Min	Max	Max	Max	Size	Type		Ordering Suffix				
		Thread Length (Metric) "E"	NPT	Thread Length (NPT) "E"	NPT																
20s16	M20	10.0	1/2"	19.9	3/4"	3.1	8.6	6.1	13.1	0.3	1.0	24.0	26.4	72.5	20S16	E1X	1RA	PVC04	0.163		
20S	M20	10.0	1/2"	19.9	3/4"	6.1	11.6	9.5	15.9	0.3	1.0	24.0	26.4	70.0	20S	E1X	1RA	PVC04	0.150		
20	M20	10.0	1/2"	19.9	3/4"	6.5	13.9	12.5	20.9	0.4	1.0	30.5	33.6	73.0	20	E1X	1RA	PVC06	0.210		
25S	M25	10.0	3/4"	20.2	1"	11.1	19.9	14.0	22.0	0.4	1.2	37.5	41.3	89.0	25S	E1X	1RA	PVC09	0.330		
25	M25	10.0	3/4"	20.2	1"	11.1	19.9	18.2	26.2	0.4	1.2	37.5	41.3	89.0	25	E1X	1RA	PVC09	0.330		
32	M32	10.0	1"	25.0	1 1/4"	17.0	26.2	23.7	33.9	0.4	1.2	46.0	50.6	86.0	32	E1X	1RA	PVC11	0.430		
40	M40	15.0	1 1/4"	25.6	1 1/2"	22.0	32.1	27.9	40.4	0.4	1.6	55.0	60.5	90.0	40	E1X	1RA	PVC15	0.620		
50S	M50	15.0	1 1/2"	26.1	2"	29.5	38.1	35.2	46.7	0.4	1.6	60.0	66.0	91.0	50S	E1X	1RA	PVC18	0.750		
50	M50	15.0	2"	26.9	2 1/2"	35.6	44.0	40.4	53.0	0.6	1.6	70.1	77.1	95.0	50	E1X	1RA	PVC21	0.950		
63S	M63	15.0	2"	26.9	2 1/2"	40.1	49.9	45.6	59.4	0.6	1.6	75.0	82.5	102.0	63S	E1X	1RA	PVC23	1.340		
63	M63	15.0	2 1/2"	39.9	3"	47.2	55.9	54.6	65.8	0.6	1.6	80.0	88.0	104.0	63	E1X	1RA	PVC25	1.340		
75S	M75	15.0	2 1/2"	39.9	3"	52.8	61.9	59.0	72.0	0.6	1.6	90.0	99.0	115.0	75S	E1X	1RA	PVC28	2.110		
75	M75	15.0	3"	41.5	3 1/2"	59.1	67.9	66.7	78.4	0.6	1.6	100.0	110.0	117.0	75	E1X	1RA	PVC30	2.420		
90	M90	24.0	3 1/2"	42.8	4"	66.6	78.6	76.2	90.3	0.8	1.6	114.3	125.4	147.0	90	E1X	1RA	PVC32	4.210		
100	M100	24.0	4"	44.0	5"	76.0	90.9	86.1	101.4	0.8	1.6	123.0	135.3	140.0	100	E1X	1RA	LSF33	4.450		
115	M115	24.0	4"	44.0	5"	86.0	97.9	101.5	110.2	0.8	1.6	133.4	146.7	162.0	115	E1X	1RA	LSF34	6.190		
130	M130	24.0	5"	46.8	6"	97.0	114.9	110.2	123.2	0.8	1.6	152.4	160.6	174.0	130	E1X	1RA	LSF35	8.340		

*Note : For material options please add the following suffix to change the Ordering Reference : Brass (no suffix required), Nickel Plated Brass "5", Copper Free Aluminium "1"
For NPT options add the following digits to the material suffix; 1/2" = 31; 3/4" = 32; 1" = 33; 1 1/4" = 34; 1 1/2" = 35; 2" = 36; 2 1/2" = 37; 3" = 38; 3 1/2" = 39; 4" = 310 (Brass requires prefix '0')

Examples: 32E1X1RA534 = Nickel Plated Brass 1-1/4" NPT, 50SE1X1RA035 = Brass 1-1/2" NPT, 20E1X1RA5 = Nickel Plated Brass M20

Dimensions are displayed in millimetres unless otherwise stated