



Pulling Eyes

Installation Accessory for Flexible Conduit and HDPE Duct

Features

- More linear threads per inch for better grip on duct
- Wider application range per size for fewer sizes to handle
- Buttressed threads hold duct more securely
- For smooth-wall, ribbed and corrugated ducts

Also known as Inner Duct Pulling Eyes or Subduct Pulling Eyes, these heavy-duty products securely connect flexible conduit and HDPE duct to swivels and winch lines.

Pulling Eyes are designed for the wide variety of flex-, sub- and inner-ducts used in telecom and utility construction. They are manufactured of solid plated steel and withstand years of abuse in the field. Hex head design provides for easy installation.

Each Pulling Eye is designed with pulling strength that exceeds the maximum pulling tension recommended by duct manufacturers.

Pulling Eyes

Installation Accessory for Flexible Conduit and HDPE Duct

Selection Guide

Part Number	Product Descriptor	Nominal Size	Duct ID Range	
			inches	mm
622396	JM-HPE-07PE095U	0.75	0.67 - 0.95	17 - 24
732020	JM-HPE-10PE118U	1.00	0.91 - 1.18	23 - 30
153014	JM-HPE-12PE142U	1.25	1.14 - 1.42	29 - 36
324774	JM-HPE-15PE173U	1.50	1.38 - 1.73	35 - 44
525566	JM-HPE-20PE228U	2.00	1.77 - 2.28	45 - 58



www.commscope.com

Visit our website or contact your local CommScope representative for more information.

© 2016 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services.

PS:XXXX-AE (04/16) previously C221.10