



Quadplex Duct Plug

Multi-Port Sealing Devices

Quadplex duct plugs are split plugs for sealing around, organizing, and supporting up to four subducts, pipes, or cables. The plugs are designed for use in round openings such as conduits, conduit fittings and core-drilled wall penetrations. Effective long-term water-tight and air-tight seals, these products also prevent mud, backfill, and slurry from entering handholes, manholes, and buildings during the construction process.

The service life of cable, splices, manhole hardware and electronics can be increased when contact with moisture is reduced. Flooded underground structures are accessed more quickly when they are isolated from the ingress of water, mud, and slurry.

Features

- Split design for retrofitting without disassembly
- Anchors and organizes subducts or multiple duct systems
- Eliminates duct-edge abrasion to cables
- Expandable gasket allows for expansion and contraction of cables or subducts without leakage
- Excellent for supporting cables at the tops of risers

When selecting a Quadplex Duct Plug:

1. Determine the inside diameter of the duct and select the range of plugs.
2. Determine the outside diameter of the cable (or inner duct) and select the correct plug in the range.
3. If the diameter of the cable (or inner duct) is below the specified range, select a plug with a bushing sleeve series reference number. Refer to the bushing sleeve data sheet and select a bushing from the series listed in the table.
4. Any unused ports in the plug can be blocked using a hole plug. Refer to the hole plug data sheet and look for a hole plug to match the bushing sleeve series.

Quadplex Duct Plug

Multi-Port Sealing Devices

Product Descriptor	Size	Duct ID Range		Cable or Duct OD Range		Part Number
		inches	mm	inches	mm	
JM-QUA-35Q118H	3.50	3.43 - 3.58	87.1 - 90.9	1.10 - 1.18	27.9 - 30.0	856874
JM-QUA-35Q126SG	3.50	3.50 - 3.62	88.9 - 91.9	1.14 - 1.26	29.0 - 32.0	193540
JM-QUA-36Q136HG	3.60	3.62 - 3.81	91.9 - 96.8	1.19 - 1.36	30.2 - 34.5	391614
JM-QUA-36Q136SG	3.75	3.70 - 3.81	94.0 - 96.8	1.19 - 1.36	30.2 - 34.5	396490
JM-QUA-40Q136H	3.80	3.86 - 4.00	98.0 - 101.6	1.19 - 1.36	30.2 - 34.5	610144
JM-QUA-40Q136SG	4.00	4.02 - 4.17	102.1 - 105.9	1.19 - 1.36	30.2 - 34.5	583840
JM-QUA-40Q142SG	4.00	4.02 - 4.17	102.1 - 105.9	1.36 - 1.42	34.5 - 36.1	467948
JM-QUA-40Q142AG	4.20	4.19 - 4.35	106.4 - 110.5	1.30 - 1.42	33.0 - 36.1	627014
JM-QUA-40Q157AG	4.20	4.19 - 4.35	106.4 - 110.5	1.42 - 1.57	36.1 - 39.8	557800
JM-QUA-40Q160AG	4.20	4.19 - 4.35	106.4 - 110.5	1.48 - 1.60	37.6 - 40.6	976712
JM-QUA-50Q142HG	4.80	4.88 - 5.00	124.0 - 127.0	1.30 - 1.42	33.0 - 36.1	834194
JM-QUA-50Q167HG	4.80	4.88 - 5.00	124.0 - 127.0	1.53 - 1.67	38.9 - 42.4	694672
JM-QUA-50Q192HG	4.80	4.88 - 5.00	124.0 - 127.0	1.77 - 1.92	45.0 - 48.8	594784
JM-QUA-50Q136SG	5.00	5.04 - 5.28	128.0 - 134.1	1.19 - 1.36	30.2 - 34.5	447282
JM-QUA-50Q142SG	5.00	5.04 - 5.28	128.0 - 134.1	1.30 - 1.42	33.0 - 36.1	944150
JM-QUA-50Q150SG	5.00	5.04 - 5.28	128.0 - 134.1	1.36 - 1.50	34.5 - 38.1	296044
JM-QUA-50Q167S	5.00	5.04 - 5.28	128.0 - 134.1	1.50 - 1.67	38.1 - 42.4	935544
JM-QUA-50Q192SG	5.00	5.04 - 5.28	128.0 - 134.1	1.77 - 1.92	45.0 - 48.8	689878
JM-QUA-60Q142HG	5.80	5.82 - 5.98	147.8 - 151.9	1.30 - 1.42	33.0 - 36.1	142324
JM-QUA-60Q167HG	5.80	5.82 - 5.98	147.8 - 151.9	1.53 - 1.67	38.9 - 42.4	314456
JM-QUA-60Q192HG	5.80	5.82 - 5.98	147.8 - 151.9	1.81 - 1.92	46.0 - 48.8	521878
JM-QUA-60Q136SG	6.00	6.02 - 6.33	152.9 - 160.8	1.19 - 1.36	30.2 - 34.5	357672
JM-QUA-60Q142SG	6.00	6.02 - 6.33	152.9 - 160.8	1.30 - 1.42	33.0 - 36.1	720508
JM-QUA-60Q167SG	6.00	6.02 - 6.33	152.9 - 160.8	1.50 - 1.67	38.1 - 42.4	634192
JM-QUA-60Q192SG	6.00	6.02 - 6.33	152.9 - 160.8	1.77 - 1.92	45.0 - 48.8	596818
JM-QUA-60Q196SG	6.00	6.02 - 6.33	152.9 - 160.8	1.84 - 1.96	47.0 - 49.8	C85095
JM-QUA-60Q216SG	6.00	6.02 - 6.33	152.9 - 160.8	1.96 - 2.16	49.8 - 54.9	930142
JM-QUA-80Q238SG	8.00	7.76 - 7.90	197.1 - 200.7	2.16 - 2.38	54.9 - 60.4	312314
JM-QUA-40Q136S-R	4.00	4.02 - 4.17	102.1 - 105.9	1.19 - 1.36	30.2 - 34.5	067610
JM-QUA-40F136SG	4.00	3.96 - 4.13	100.6 - 104.9	1.22 - 1.36	31.0 - 34.5	273228
JM-QUA-40F142SG	4.00	3.96 - 4.13	100.6 - 104.9	1.30 - 1.42	33.0 - 36.1	711508
JM-QUA-40Q160AG-1	4.15	4.19 - 4.35	106.4 - 110.5	(2x)1.48 - 1.60	37.6 - 40.6	F64550
				(2x)1.10 - 1.26	27.9 - 32.0	
JM-QUA-40Q160SG-1	4.00	4.02 - 4.17	102.1 - 105.9	(2x)1.48 - 1.60	37.6 - 40.6	E23128
				(2x)1.10 - 1.26	27.9 - 32.0	
JM-QUA-45Q160SG-1	4.50	4.61 - 4.80	117.1 - 121.9	(2x)1.48 - 1.60	(2x) 37.6 - 40.5	E27292
				(2x)1.14 - 1.26	(2x) 29.0 - 32.0	



www.commscope.com

Visit our website or contact your local CommScope representative for more information.

© 2016 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services.

PS-315160.1-AE (04/16)