



## Termination Connector

### Female-to-Male Threaded Connectors

---

These female-to-male threaded connectors are designed to secure inner duct to cabinets and junction boxes. They consist of a universal threaded coupling end and a nipple end with locking washers and gaskets. The connectors attach to standard knockout sizes in panels and racking for maximum security to premises cabling, eliminating cable kink at these transitions.

### Features

- Rugged construction
- Color-coded sizing
- Toolless installation
- Eliminates cable kink at pull-box or cabinets
- Aircraft grade AA 6061 aluminum

## Termination Connector

### Female-to-Male Threaded Connectors

---

## Ordering Information

Product Descriptor	Size	inches (mm)	inches (mm)	Color	Part Numbers
JMHC-10IC142U	1.0	1.375" (35.00 mm)	1.18" - 1.42" (30.0 - 36.0 mm)	Aluminum	151046-000
JMHC-12IC170U	1.25	1.625 - 1.75" (41.3 - 44.5 mm)	1.46" - 1.70" (37.0 - 43.2 mm)	Burgundy	134628-000
JMHC-15IC200U	1.5	2.000" (50.00 mm)	1.78" - 2.00" (45.0 - 50.8 mm)	Navy Blue	460208-000
JMHC-20IC252U	2.0	2.500" (63.50 mm)	2.28" - 2.52" (57.9 - 64.0 mm)	Bronze	626810-000



[www.commscope.com](http://www.commscope.com)

Visit our website or contact your local CommScope representative for more information.

© 2016 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services.

PS-315158.2-AE (4/16)