

Description

ComPact 1200 AC/DC is a compact DC power supply and battery charger with nominal output of 28V/40A. It is a mechanically and electrically rugged unit capable of operating under harsh environmental conditions with large input voltage variations. ComPact 1200 AC/DC is a high efficiency unit designed to supply power to sensitive electronics, with or without backup battery. The input current is power factor corrected and designed for optimum utilization of weak power sources such as portable generators.



NSN 6130-25-160-4349

The efficiency is very high due to soft switching technology. The ComPact can operate stand alone or be mounted in 19" rack systems that occupies 2U (88.9mm/3.5") height. ComPact 1200 AC/DC has an RS485 port that can be used for control, monitoring and setup. Detailed status and statistics can be retrieved over this port. The signal connectors provides several signals: Alarm relay outputs, external battery temperature sensing and a bus for interconnection of multiple units in a redundant or parallel system. ComPact 1200 AC/DC can be configured to charge different battery technologies such as LI-Ion, NiMH, NiCd and Lead acid. The unit is software-upgradeable for future battery technologies. Temperature compensated charging ensures full battery capacity over entire temperature range. The unit is protected from over voltage, short circuit, over current and over temperature. ComPact 1200 AC/DC can be software configured according to customer specification.

Functions	
Over temperature	The unit is protected from over temperature. The unit shuts down at an ambient temperature of 80°C, free standing unit. The unit automatically starts up again when the temperature drops.
Input circuit breaker	The input circuit breaker releases if the input current exceeds 15A and the unit shuts off.
Alarms	Status signals are fed to separate potential free outputs, and are indicated in separate LEDs for: Power OK Unit alarm Current limit
Display	The display can be toggled between output voltage and output current
Input voltage	When the input voltage is below the safe operating range, the converter is shut off. When the voltage returns, the converter is turned on again.
Connectors	AC input: 3102E-16-10P (Threaded) DC output: 3102E-22-2S (Threaded) Alarm 1: Binder 09-0404-30-02 Alarm 2: Binder 09-0412-30-04 NTC/PAR/COM: 2 pieces. Binder 09-0416-30-05
Grounding	Available in front
Acoustic noise	At ambient temperatures below 45°C the acoustic noise is 45 dBA.
Frequency range	45 - 430Hz
Cooling	Forced air by temperature controlled fan

ComPact 1200 AC/DC

Specification

Electrical data at 50Hz input voltage	
Input voltage	99 – 276 VAC
Power Factor (PF)	Typical 0.99 @ full load
Input current at max load and 50Hz	14A @ 99 VAC 12A @ 115 VAC 6A @ 230 VAC
Total Harmonic Distortion (THD) @ 28V 40A, 230V 50Hz	Typical 12%
Efficiency at full load	> 88% @ 115 VAC > 90% @ 230 VAC
Nominal output voltage	28 VDC
Adjustable output voltage	20.0 - 34.0 VDC
Nominal output current	40A
Adjustable current limit	5 – 40 Amps
Short circuit current	≤44.0 Amps
Load sharing	Max 3 Amps deviation
Output voltage ripple and noise	<100mV p-p, 20MHz bandwidth
Output voltage regulation	<1.5% zero/max load

Standards
<p>Electromagnetic Interference The power supply meets the requirements of MIL-STD-461E and F; Ground Army; CE101, CE102, RE101 RE102, RS103, CS101, CS114, CS115 and CS116</p>
<p>Electrical systems in vehicles MIL-STD-1275D</p>
<p>Electrostatic discharge The power supply meets the requirements of EN 61000-4-2 for ESD</p>
<p>Safety Designed to meet EN 60950</p>
<p>Encapsulation IP67</p>

Product	Part No.	NSN
Compact 1200 AC/DC	P600380	6130-25-160-4349

Environmental
<p>High temperature <u>Operation</u> MIL-STD-810G: Method 501.5, Procedure II, 60°C <u>Storage</u> MIL-STD-810G: Method 501.5, Procedure I, 71°C</p>
<p>Low temperature <u>Operation</u> MIL-STD-810G: Method 502.5, Procedure II, -40°C <u>Storage</u> MIL-STD-810G: Method 502.5, Procedure I, -51°C</p>
<p>Temperature shock MIL-STD-810G: Method 503.5, -51°C - +71°C. (Non-operational)</p>
<p>Humidity MIL-STD-810G: Method 507.5, Procedure II</p>
<p>Vibration MIL-STD-810G, Method 514.6C Table 514.6C-VI. Composite wheeled vehicle vibration exposures figure 514.6C-3 . MIL-STD-801G, Method 514.6D, Ground Vehicle Category 20, Wheeled/Tracked/Trailer, Procedure I/III</p>
<p>Shock MIL-STD-810G, Method 516.6, Procedure I, functional Shock, 40g 11ms</p>
<p>Fungus Analysis of the degree of inertness to fungus growth of the components in accordance with MIL-HDBK-454</p>
<p>Altitude MIL-STD-810G, Method 500.5, Procedure I (Storage) and II (Operational) Test altitude is 4750m(15000ft) at 57.2Kpa for Operational and 12195m (40000ft.) at 18.8Kpa. for Storage.</p>

Mechanical Data	
Dimensions:	
Width	220mm, 8.66"
Depth in rack	390mm, 15.35"
Depth total	420mm, 16.54"
Height	88mm, 3.5" (2U)
Weight	11.1kg, (24.5lbs)
Mounting:	Any direction and in 19" rack