# Simplifying software development to maximize return on investment

TEXAS INSTRUMENTS

Henry Wiechman Embedded Processor Software Marketing and Strategy Texas Instruments

Adrian Fernandez Microcontroller Development Experience Manager Texas Instruments

### **Overview**

The software challenges associated with embedded systems development have grown significantly in recent years. These systems continue to add advanced functionality with higher speed interfaces and multiple connectivity options, driving the need for more sophisticated scheduling algorithms and increased power consumption and code size. End-product needs are also changing rapidly as companies strive to serve multiple markets with different adaptations of their base product. As time-to-market windows shrink, developers need a robust software foundation with intuitive levels of abstraction and operating system support to enable faster creation of applications. This foundation should support a broad portfolio of devices that can easily reuse application code so that initial investments can be ported to a variety of products with varying system requirements.

The SimpleLink<sup>™</sup> microcontroller (MCU) software development kit (SDK) is a complete set of validated, fully documented drivers, stacks and code examples that enable engineers to develop innovative and differentiated applications with the <u>SimpleLink</u> <u>connected-MCU family</u> from Texas Instruments (TI). This powerful SDK provides a cohesive and consistent experience by packaging essential software components and easy-to-use examples in one comprehensive package. Everything a customer needs to quickly and efficiently develop new applications using an ARM<sup>®</sup> Cortex<sup>®</sup>-M-based MCU from TI is included in the SDK, from the drivers and communication stacks to an OS kernel. The SDK is also well integrated into the <u>development environment</u> making advanced debug capabilities easily accessible.

This cohesive experience across SimpleLink SDKs allows developers to spend their time creating applications that differentiate products from competitors. TI's SimpleLink portfolio is a fully tested and integrated, out-of-the-box robust solution. And through 100 percent code portability, the common foundation of the SDK maximizes reuse. TI's ongoing commitment to the platform guarantees compatible APIs. In addition, the common components of the SDK are available under industry-standard, open-source licensing models that enable customer use directly in applications.

2

## How the SimpleLink SDK improves the development cycle

Designing new products and applications is not as easy as it may seem. Developing new products from the ground up can require a large investment in tools, software and time to learn the new design environment. How easy are the new tools to use? Are they well documented? Does training exist to help designers ramp-up faster? What kind of APIs does the software use? Are they industry-standard or proprietary and changing? How extensive is the underlying silicon portfolio that is supported? How will the software and tools be supported? When these ramp-up challenges are considered, along with the need to be nimble and able to adapt quickly to ever-changing customer needs and wants, developers can quickly become overwhelmed.

TI's SimpleLink MCU SDK enables rapid development and simplified porting across the industry's broadest portfolio of connected MCUs, providing flexibility within the portfolio as customer needs and connectivity standards requirements evolve. The SDK supports all devices in the SimpleLink MCU portfolio, including:

- MSP432<sup>™</sup> MCU: Ultra-low-power ARM Cortex-M4F-based MCUs with 14-bit SAR ADC optimized for wireless host MCU and capturing and processing high-precision analog signals.
- <u>CC32x0</u> devices: ARM Cortex-M4-based MCUs with integrated Wi-Fi<sup>®</sup> and advanced security features.
- CC2640R2F and CC1310/CC1350 wireless
   MCUs: Low-power wireless ARM Cortex-M3-based MCUs for high-performance RF applications. These devices support a range of wireless standards, including *Bluetooth*<sup>®</sup> low energy and Sub-1 GHz-based standards such as Wireless M-Bus, SigFox and 6LoWPAN, and dual-band capability. There is also planned support for zigbee<sup>®</sup> and Thread.

The SimpleLink SDK maximizes developers' return on investment. As displayed in **Figure 1** below, the SDK allows designers to develop an application on one SimpleLink MCU, such as the MSP432P401R device, and then reuse the application on a different



Figure 1. Application scalability examples

SimpleLink MCU, like the CC3220 wireless MCU, to add new functionality without starting from scratch. A comprehensive suite of TI Drivers combined with a POSIX-compliant API and integrated RTOS support streamlines integration and ensures compatibility with numerous third-party software components.

In a typical development scenario, a customer might initially introduce a stand-alone ultra-low-power thermostat using the SimpleLink MSP432 MCU. As their business grows and customer demands change, the customer sees the need for a Wi-Fienabled thermostat to allow end users to leverage Wi-Fi connectivity for home automation. They can then design a new application based on the SimpleLink CC3220 wireless MCU or host MSP432 MCU and CC3120 wireless network processor. All thermostat control software, user interfaces and applications that were developed for the MSP432 MCU-based thermostat are 100 percent reusable for the new Wi-Fi-based thermostat. This allows the customer to easily add Wi-Fi to their existing product without having to start over.

Down the road, if the customer releases a Bluetooth low energy thermostat for phone pairing, all that software is again portable to a CC2640R2F wireless MCU solution with or without the host MSP432 MCU. Even when moving to a gateway sensor network in an industrial setting the same software developed for the stand-alone thermostat can still be used in the Sub-1 GHz sensor network application using the CC1310 device. This application could also incorporate a dual-band CC1350 wireless MCU, which enables Bluetooth low energy connection to a smart phone in the same device.

TI recognizes that customers need software they can count on and that they know will be usable now and in the future. TI's SimpleLink SDK will regularly release software updates so designers have a predictable upgrade path with upward API code compatibility. All SDK components are fully integrated and tested together to provide a robust foundation for application development. And the SimpleLink SDK is developed, maintained and directly supported by TI through the 24/7 E2E<sup>™</sup> <u>community</u> as well as hands-on <u>SimpleLink</u> <u>Academy</u> training to make sure you are supported along every step of your design.

#### SimpleLink MCU SDK: The breakdown

TI's <u>SimpleLink MCU SDK</u> (Figure 2) is a complete, out-of-the-box solution for all your development needs. The SDK allows you to spend your time building differentiated applications without worrying about creating pieces like communication stacks or developing drivers from the ground up.



Figure 2. SimpleLink SDK components

#### **TI drivers**

The TI drivers API exposes the functionality of the hardware-specific drivers in the same way across all TI SimpleLink devices, giving developers portable, feature-rich access to a variety of peripherals. TI drivers are open source [Berkeley Software Distribution license (BSD)] and built on the hardware abstraction layer, offering full access to the device's complete capability. For example, though the hardware implementation of the UART may be different across each devices, the TI drivers API used to access its common functionality is the same.

This device-agnostic approach provides easy portability of the application code across SimpleLink devices now and into the future. Other peripherals exposed through these intuitive and consistent TI driver APIs include analog-to-digital converter (ADC), SPI, PWM and GPIO, among many others. With full access to the hardware abstraction layer through the TI drivers, developers can further optimize their applications by leveraging the Hardware Abstraction Layer (HAL) or directly accessing the microcontroller with register-level programming. TI drivers allow customers to make the application exactly what it needs to be.

#### **OS/kernel**

The kernel provides real-time, multitasking services such as timing and scheduling of tasks. All TI SimpleLink SDKs come with the TI-RTOS kernel pre-installed and are POSIX-compliant. TI-RTOS is a robust solution you can trust, already deployed in thousands of applications across various TI embedded solutions. The kernel is open source (BSD license) and was developed in lock-step with TI's silicon portfolio to enable very low latency in an efficient code footprint. Developers can optimize applications for power consumption, performance and code size to meet their needs. SimpleLink SDKs also support alternative RTOS kernels, such as FreeRTOS. The RTOS kernel runs the hardware abstraction layer as well as a suite of functional drivers for all on-chip peripherals.

The **POSIX** layer abstracts the RTOS kernel functionality used by applications. POSIX is an IEEE industry standard for compatibility between operating systems. Requiring less than 2 KB of code in typical applications, the POSIX layer allows examples and user applications to be easily re-used and ported to a different kernel. Using this layer is optional but allows customers to use whatever OS they are currently familiar with or want to move to in the future. POSIX-compatibility also allows TI third-party partners to interface with SimpleLink SDK devices to add support for their kernel. This provides complete freedom to design with any OS, including FreeRTOS.

#### **Middleware**

TI's middleware adds functionality on top of drivers. Communication stacks and graphics libraries are just two examples of middleware. TI has completed all testing and integration of this middleware for SimpleLink devices, making it fast and easy to integrate new technologies like Wi-Fi or Bluetooth low energy into an application. Some examples of middleware included for each of the SimpleLink SDK devices are shown in **Figure 3** below.

Device	CC3220	CC2640R2F	CC13x0	MSP432
Included Middleware Stacks and Libraries	• Wi-Fi	<ul> <li>Bluetooth low energy</li> </ul>	• EasyLink Sub-1 GHz RF	<ul> <li>IQ math</li> <li>Graphics library</li> </ul>

Figure 3. Middleware to support each unique SimpleLink device

#### **SDK plug-ins**

The SimpleLink SDK was built to provide a consistent platform for developers to build their applications. This consistent platform makes it easy for TI, third parties or even community members to develop plug-ins that depend on the TI SimpleLink SDK to support external components. Initially, the SimpleLink MSP432 SDK will be complemented by the Bluetooth low energy and Wi-Fi plug-ins for connectivity. TI's plug-in offerings will continue to expand to include sensors, actuators, displays and more, enabling developers to build complex systems quickly with this modular software approach.

#### Hardware abstraction layer (HAL)

The hardware abstraction layer (HAL) consists of C functions that abstract writes to hardware registers. The TI drivers and OS kernel are built using the HAL to access hardware features. The HAL, built on top of device-specific header files, follows the ARM CMSIS standard, simplifying access to device modules beyond the register level. With the DriverLib HAL access, developers can peel back the layers of the TI drivers for greater control of their applications or to enhance the software for peripheral and devicespecific optimization.

#### **Examples and training**

The SDK provides a wide range of free examples. Using these examples, customers can quickly and easily start writing applications straight out of the box. Each example comes with its own documentation and project files, giving you everything you need to get started. Examples are provided using the supported RTOS kernels. For certain SDKs, examples that do not use an RTOS are also provided.

Freely accessible to all customers, the SimpleLink Academy delivers dozens of exercises and workshops to help get you designing applications quickly. SimpleLink Academy curated trainings support developers of all experience levels to help them get the most out of these devices.

#### Conclusion

Developers today face a myriad of challengesrapidly expanding functionality and connectivity requirements coupled with continued pressure on power, code size and time-to-market. A robust and intuitive software foundation is necessary to expedite initial development. This foundation should support a portfolio of devices that can enable a range of different system configurations while leveraging the initial investment. By enabling 100 percent code portability and a common foundation, the SimpleLink MCU SDKs maximize reuse and portability across devices today and into roadmap devices of the future. This ultimately saves time and money, allowing designers to concentrate on developing differentiated applications. The common software platform also allows designers to easily expand and add functionality that fits new markets.

TI's SimpleLink SDK plug-ins further extend the functionality of products with external components and software, including connectivity stacks, sensors, actuators and more. These plug-ins are built on top of the TI drivers included in the SDK and are available directly from TI as well as third-party developers.

To stay up-to-date on the latest SimpleLink SDK devices, plug-ins, etc. be sure to visit www.ti.com/simplelink.

Important Notice: The products and services of Texas Instruments Incorporated and its subsidiaries described herein are sold subject to TI's standard terms and conditions of sale. Customers are advised to obtain the most current and complete information about TI products and services before placing orders. TI assumes no liability for applications assistance, customer's applications or product designs, software performance, or infringement of patents. The publication of information regarding any other company's products or services does not constitute TI's approval, warranty or endorsement thereof.

The platform bar, E2E, MSP432 and SimpleLink are trademarks of Texas Instruments. All other trademarks are the property of their respective owners.



#### IMPORTANT NOTICE FOR TI DESIGN INFORMATION AND RESOURCES

Texas Instruments Incorporated ('TI") technical, application or other design advice, services or information, including, but not limited to, reference designs and materials relating to evaluation modules, (collectively, "TI Resources") are intended to assist designers who are developing applications that incorporate TI products; by downloading, accessing or using any particular TI Resource in any way, you (individually or, if you are acting on behalf of a company, your company) agree to use it solely for this purpose and subject to the terms of this Notice.

TI's provision of TI Resources does not expand or otherwise alter TI's applicable published warranties or warranty disclaimers for TI products, and no additional obligations or liabilities arise from TI providing such TI Resources. TI reserves the right to make corrections, enhancements, improvements and other changes to its TI Resources.

You understand and agree that you remain responsible for using your independent analysis, evaluation and judgment in designing your applications and that you have full and exclusive responsibility to assure the safety of your applications and compliance of your applications (and of all TI products used in or for your applications) with all applicable regulations, laws and other applicable requirements. You represent that, with respect to your applications, you have all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. You agree that prior to using or distributing any applications. TI has not conducted any testing other than that specifically described in the published documentation for a particular TI Resource.

You are authorized to use, copy and modify any individual TI Resource only in connection with the development of applications that include the TI product(s) identified in such TI Resource. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information regarding or referencing third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of TI Resources may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI RESOURCES ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING TI RESOURCES OR USE THEREOF, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY YOU AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS EVEN IF DESCRIBED IN TI RESOURCES OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF TI RESOURCES OR USE THEREOF, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

You agree to fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of your noncompliance with the terms and provisions of this Notice.

This Notice applies to TI Resources. Additional terms apply to the use and purchase of certain types of materials, TI products and services. These include; without limitation, TI's standard terms for semiconductor products <a href="http://www.ti.com/sc/docs/stdterms.htm">http://www.ti.com/sc/docs/stdterms.htm</a>), evaluation modules, and samples (<a href="http://www.ti.com/sc/docs/stdterms.htm">http://www.ti.com/sc/docs/stdterms.htm</a>), evaluation

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2017, Texas Instruments Incorporated