

EB-9000S






Soldering & Rework Station



EB-9000S COMPONENTS

EB-9000PS	Power Supply
SHH-1	Soldering Handpiece Holder
SHP-1	Soldering Handpiece
RMP-1	Tip Removal Pad
SG-1-GR	Handpiece Grip Green
SG-1-GY	Handpiece Grip Gray
BC-1	Brass Curls
SPG-1	Sulphide Free Sponge
M7CH176	Soldering tip cartridge


EB-9000S SPECIFICATIONS

Input Line Voltage: EB-9000PS	100-110 VAC
EB-9000PS-2	220-240 VAC
Tip to Ground Potential:	<2mV, true RMS 50-500Hz
Tip to Ground Resistance:	<2 Ohms DC
Idle temperature Stability:	+/- 1.1 °C (2 °F)
Maximum Enclosure Temperature:	50 °C (122 °F)
Fuse: EB-9000PS	125V 1A "Slo-Blo"
EB-9000PS-2	250V 0.5A "Slo-Blo"
Output Frequency:	13.56 MHz
Size (W x H x D):	212.4mm x 118mm x 132mm
Weight:	3.47 KG
LCD display:	60mm x 16mm
Input Line Frequency:	50/60 Hz
Certification marks:	    

ACCESSORY - DESOLDER GUN




DS-KIT-1




Part Number	A		B	
	MM	IN.	MM	IN.
EBM75DT004	1.0	0.04"	1.6	0.06"
EBM75DT005	1.3	0.05"	2	0.08"
EBM75DT006	1.5	0.06"	2.3	0.09"

EB-9000S

EBM Series Tip Cartridges




CHISEL




CONICAL

Part Number	A		C	
	MM	IN.	MM	IN.
EBM7CH175	2.50	0.10"	10.00	0.39"
EBM7CH176	1.78	0.07"	10.00	0.39"
EBM7CH177	1.50	0.06"	10.00	0.39"
EBM7CH178	1.00	0.04"	9.00	0.35"
EBM7CH179	1.00	0.04"	6.40	0.25"
EBM7CH180	3.00	0.12"	8.90	0.35"
EBM7CH181	3.00	0.12"	5.20	0.20"
EBM7CH250	5.00	0.20"	7.50	0.30"
EBM7CP200	2.50	0.10"	6.40	0.25"
EBM7CP201	1.80	0.07"	6.40	0.25"
EBM7LC650	5.00	0.20"	11.40	0.45"
EBM7LR403	1.78	0.07"	15.00	0.59"

Part Number	A		C	
	MM	IN.	MM	IN.
EBM7C300	0.40	0.016"	14.00	0.55"
EBM7C301	0.50	0.02"	5.00	0.20"
EBM7CP302	0.40	0.016"	8.90	0.35"
EBM7CP303	1.00	0.04"	7.40	0.29"
EBM7CS150	0.40	0.016"	13.00	0.51"
EBM7CS151	1.00	0.04"	13.40	0.53"
EBM7CS152	0.40	0.016"	8.50	0.33"
EBM7CS154	1.00	0.04"	16.40	0.65"
EBM7CS155	0.50	0.02"	15.40	0.61"
EBM7MF375	0.25	0.01"	13.40	0.53"




BEVEL




CHISEL BENT

Part Number	A		C	
	MM	IN.	MM	IN.
EBM7BV350	1.78	0.07"	14.00	0.55"
EBM7BS602	1.80	0.07"	6.40	0.25"
EBM7LR400	1.00	0.04"	14.60	0.57"

Part Number	B		C	
	MM	IN.	MM	IN.
EBM7CB225	1.78	0.07"	10.00	0.39"
EBM7CB226	1.50	0.06"	12.00	0.47"




CONICAL BENT




KNIFE

Part Number	B		C	
	MM	IN.	MM	IN.
EBM7B325	0.40	0.016"	16.00	0.63"
EBM7MD575	0.51	0.02"	15.40	0.61"
EBM7SB275	0.40	0.016"	8.40	0.33"
EBM7SB276	0.50	0.02"	14.00	0.55"

Part Number	B		C	
	MM	IN.	MM	IN.
EBM7DS526	4.83	0.19"	16.00	0.63"
EBM7K100	4.83	0.19"	16.40	0.65"



HOOF



BLADE

Part Number	B		C	
	MM	IN.	MM	IN.
EBM7DS525	3.30	0.13"	17.90	0.70"
EBM7DS529	1.52	0.06"	16.40	0.65"
EBM7LR401	3.05	0.12"	16.40	0.65"
EBM7WV300	3.00	0.12"	14.50	0.57"

Part Number	A		B		C	
	MM	IN.	MM	IN.	MM	IN.
EBM7LB125	10.41	0.41"	2.00	0.08"	9.00	0.35"
EBM7LB126	15.75	0.62"	2.00	0.08"	9.00	0.35"
EBM7LB127	22.10	0.87"	2.00	0.08"	9.00	0.35"
EBM7LB128	30.00	1.18"	2.00	0.08"	9.00	0.35"

6 = Temperature Sensitive 7 = Standard Applications 8 = High Performance

