


ONYX

Versatile mission computer for Vetrronics & Avionics applications



▶ RTCA DO & MIL-STD qualified COTS rugged modular mission computers to cut time, budget and design risk

ONYX consists of fully integrated computing subsystems ready for deployment in SWaP-C extreme environment. It allows the unit to fit easily into available nooks on any platform making it ideal for space constrained applications such as ground vehicles, manned & unmanned aircrafts, helicopters, UAS or any other robots in harsh environment requiring rock-solid reliability.

Qualified ONYX systems slash design risk, lower costs and speed deployment thanks to risk-lowering of proven technology, stress tests passed for maximum loads, saving up to \$60,000 and 2 months campaign, reducing smaller parts inventory to simplify LRU obsolescence management.

ONYX is based on modular mezzanines concept that offers customer a large flexibility and Long Life Management under revision control. It employs leading edge dual or quad-core Intel® Haswell or Skylake processing capabilities to meet a wide variety of civilian and military tactical mission programs. ONYX is ideal for high performance harsh environment/space constrained applications, and features flexible I/O which can be tailored to customer requirements, with just a few NRE allowing customer to accelerate Time-to-Market with optimized TCO.

Particularly attention has been made on reliability and thermal management. Internal I/O routing from the backplane to the front panel MIL-DTL-38999 connectors is by means of solid-state transition module. It provides cable-free higher reliability and improved signal integrity.

> Supports Multi-Core INTEL i7 3rd, 4th and 6th Gen, evolutionary thanks to COM Express architecture with perspective of Long Life Management

> MXC GPGPU mezzanine dedicated for powerful Graphics (DVI-D, SD/HD-SDI...), Video capture, intensive computing

> VGA and other legacy display interfaces on demand (STANAG 3350 or analog RGBHV...)

> H.264/AVC Encoding and streaming capabilities

> PMC and mini PCI Express sites for flexible I/O expansion and Wireless functions

> Cable-free, Fan less, MIL-DTL-38999 circular connectors

> Real cold start at -40°C and up to +71°C Operating Temp (depend on configuration and cooling system)

> Standard BOM Qualified MIL-STD-810G/461F/1275D/704/DO-160F



> IP-67 Ingress

> High flexibility to Modified COTS Services (functions & connectors)

> ITAR free without Export Control

System specifications

Processor Module	COM-Express Basic Size
Processor 6 th Generation Intel	Mobile 6 th Generation Intel® Xeon® and Core™ Processors - 14nm ("Skylake-H") Xeon® E3-1505L v5 2.0/2.8GHz (Turbo), 0.35-1.0GHz (Graphics), 8M, 25W (4C/GT2) Core™ i7-6822EQ 2.0/2.8GHz (Turbo), 0.35-1.0GHz (Graphics), 8M, 25W (4C/GT2)
Memory	Dual channel 1867/2133 MHz DDR4 memory up to 32GB
Processor 4 th Generation Intel	4 th Generation Intel® Core™ i7 Processors (Mobile) - 22nm ("Haswell") i7-4860EQ 2.4 GHz (3.2 GHz Turbo), 47W (4C/GT3) i5-4400E 2.7 GHz (3.3 GHz Turbo), 37W (2C/GT2) i5-4402E 1.6 GHz (2.7 GHz Turbo), 25W (2C/GT2)
Memory	Dual channel with ECC 1600/1333 MHz DDR3L memory up to 16GB
Processor 3 rd Generation Intel	3 rd Generation Intel® Core™ i7/i3, 22nm process, ("Ivy Bridge") i7-3612QE 2.1GHz, 6MB L3 cache, 35W, quad core i7-3555LE 2.5GHz, 4MB L3 cache, 25W, dual core i7-3517UE 1.7GHz, 4MB L3 cache, 17W, dual core
Memory	Dual channel ECC 1600 MHz DDR3 memory up to 16 GB
Video outputs (Intel HD Graphic)	1x VGA* + 1x DVI-D Single Link
Other video Inputs / Outputs	Using MXC or miniPCIe cards
Ethernet	3x 10/100/1000 BaseT
Serial	4x RS232/RS422/RS485 (software configurable)
USB 2.0	4x USB2.0 High / Full / Low speed
USB 3.0 (38999 USB Field)	With miniPCIe card. Limited to 250MBytes /sec, on rear panel
Audio	Intel® High Def Audio: 1x In and 1x Out Lines
Discret I/O	8x GPIO LV TTL - Reset, Power Button, Power Led, HDD Led, Fast Erase
I/O Expansion slots	1x PMC slot 1x miniPCIe slot
GP-GPU Expansion slot	1x MXC site available
Solid State Disk (SSD) (Internal)	1x SSD 2.5" slot (MLC or SLC) - 1x cFast slot (MLC or SLC)
Hardware monitoring	Voltages, CPU, GPU, and carrier board temperatures
Watchdog timer	Programmable timer range to generate RESET



- A: Power supply
- B: USB, Serial, GPIO, DVI-D + VGA
- C: Ethernet, Audio
- D: GPGPU I/O
- E: PMC I/O's
- F: Ground

Power supply

Power Input	+28VDC (+10VDC up to +36VDC) Hold-up capacitors for momentary power interruption protection (approx 120ms) MIL-STD-1275D / DO-160F / MIL-STD-461F / MIL-STD-704
Power consumption	Less than 90W

SWaP-C constraints

Size (WxDxH)	270mm x 250mm x 88mm (2U)
Weight	7kg
Cooling type	Convection & radiation by fins, conduction by cold plate (conduction cooled inside)
Connectors	Military circular IP67 locking connectors (MIL-DTL-38999) Front panel customizable for specific application

Environmental Qualification Tests

Operating temperature	-40°C / +71°C (depend on configuration and cooling system)	Salt fog	50% salt spray / 96h (DO-160F)
Storage temperature	Storage: -40°C / +85°C	Dust	Wind and fine dust particles (DO-160F)
Ingress protection rating	IP67	Operating shock & vibration	MIL-STD-810G / DO-160F
Altitude	Up to 15000 feet (DO-160F)	EMI / RFI	MIL-STD-461F / DO-160F
Humidity	0%-95% relative humidity (DO-160F)	CE certification	EMC: 2014/30/UE ; EN 61000-6-2, EN55022, EN 55024 - SAFETY: 2014/35/UE ; EN60950-1 : 2006 2 nd edition A11 : 2009 + A1 : 2010 + A12 : 2011 + A2 : 2014

Software corner

Operating system	Windows 7 32/64-bit, Linux 32/64-bit, PikeOS. For other requirements, contact ECRIN Systems
-------------------------	---

Security & dependability

Trusted platform module	Atmel AT97SC3204; TPM 1.2/2.0 (TPM 2.0 release later)
Built-In-Test	pBIT, monitoring functions library, Maintenance L2 with SEMA library

Export control classification

	ITAR Free - Not Controlled (ECCN 4A003)
--	---

Other specifications

Reliability	Designed and manufactured using ISO 9001:2000 Certified Quality Program
MTBF	Calculated per MIL-HDBK-217F, available upon request
Regulatory compliance	European CE Mark
Warranty	1 year return to depot warranty (extended warranty available with service contract)
Starter cable set	Optional starter breakout cable set mates with MIL-DTL-38999 connectors to break out standard CPU I/O and power signals to traditional PC style interfaces for lab or bench testing purposes

* Not available with Skylake processor

Note: The information in this document is subject to change without notice and should not be considered as a commitment by ECRIN Systems. While reasonable precautions have been taken, ECRIN Systems assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective owners.

sales@ecrin.com

www.ecrin.com

Headquarters

143, rue Louis Neel
Parc Technologique du Pré Roux
38920 Crolles - France
Tel: +33 (0)4 76 92 20 01

Marketing & sales

2 - 12, rue du Chemin des Femmes
Immeuble l'Odyssée
91300 Massy - France
Tel: +33 (0)1 69 07 83 22

