


SUB-MINIATURE SILICON HIGH VOLTAGE FAST RECOVERY RECTIFIER

INCHES

DIM.	MIN.	MAX.
A	.019	.022
B	.120	.125
C	.395	.405
D	.875	



PART NUMBER	PIV VOLTS	I_O ma 40° C	$V_f I_O$ @ 25° C	I_r @ PIV @ 25° C	MAX SINGLE CYCLE SURGE CURRENT
BT757-10	1000	100	7	2 uA	25 AMPS
BT757-20	2000	100	7	2 uA	25 AMPS
BT757-30	3000	100	7	2 uA	25 AMPS
BT757-40	4000	50	10	2 uA	25 AMPS
BT757-50	5000	50	10	2 uA	25 AMPS
BT757-60	6000	25	15	2 uA	25 AMPS
BT757-70	7000	25	15	2 uA	25 AMPS
BT757-80	8000	25	18	2 uA	25 AMPS
BT757-100	10000	25	23	2 uA	25 AMPS
BT757-120	12000	25	23	2 uA	25 AMPS
BT757-150	15000	25	38	2 uA	25 AMPS
BT757-180	18000	25	42	2 uA	25 AMPS
BT757-200	20000	25	45	2 uA	25 AMPS

RECOVERY TIME: $I_O = 2\text{mA to } 4\text{mA to } 1\text{ mA} - 100\text{ n SEC.}$

(203) 467-2591 TEL

(203) 469-5928 FAX

Email: info @ edal.com

Internet: <http://www.edal.com>

EDAL industries, inc.

51 Commerce St. East Haven, CT 06512