

RBV3500 - RBV3510

PRV : 50 - 1000 Volts

Io : 35 Amperes


FEATURES :

- * High current capability
- * High surge current capability
- * High reliability
- * Low reverse current
- * Low forward voltage drop
- * High case dielectric strength of 2000 V_{DC}
- * Ideal for printed circuit board
- * Very good heat dissipation
- * **Pb / RoHS Free**

MECHANICAL DATA :

- * Case : Reliable low cost construction utilizing molded plastic technique
- * Epoxy : UL94V-O rate flame retardant
- * Terminals : Plated lead solderable per MIL-STD-202, Method 208 guaranteed
- * Polarity : Polarity symbols marked on case
- * Mounting position : Any
- * Weight : 8.17 grams (Approximaly)

SILICON BRIDGE RECTIFIERS



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.
 Single phase, half wave, 60 Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

RATING	SYMBOL	RBV 3500	RBV 3501	RBV 3502	RBV 3504	RBV 3506	RBV 3508	RBV 3510	UNIT
Maximum Recurrent Peak Reverse Voltage	V _R RM	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V _R MS	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _D C	50	100	200	400	600	800	1000	V
Maximum Average Forward Current T _c = 55°C	I _F (AV)	35							A
Peak Forward Surge Current Single half sine wave Superimposed on rated load (JEDEC Method)	I _F SM	400							A
Current Squared Time at t < 8.3 ms.	I ² t	660							A ² S
Maximum Forward Voltage per Diode at I _F = 17.5 A	V _F	1.1							V
Maximum DC Reverse Current at Rated DC Blocking Voltage	T _a = 25 °C	I _R							μA
	T _a = 100 °C	I _R (H)							μA
Typical Thermal Resistance (Note 1)	R _θ JC	1.5							°C/W
Operating Junction Temperature Range	T _J	10							°C
Storage Temperature Range	T _{STG}	- 40 to + 150							°C

Notes :

1. Thermal Resistance from junction to case with units mounted on heatsink.

RATING AND CHARACTERISTIC CURVES (RBV3500 - RBV3510)

FIG.1 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL FORWARD CHARACTERISTICS PER DIODE




FIG.4 - TYPICAL REVERSE CHARACTERISTICS PER DIODE

