

DECLARATION of PERFORMANCE
according to Annex III of the regulation (EU) Nr. 305/2011 (construction product regulation)
Nr. 014/15-0231/2015/01

- 1.) Unique identification code of the product-type:
EJOT SDF-K/-S plus 8UB
- 2.) Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
type and lot number are displayed on the packaging
- 3.) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
Screwed-in anchor for fixing of external thermal insulation composite systems with rendering in concrete and masonry, using category: A,B,C
Anchor length: 80 - 300 mm
- 4.) Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
EJOT Baubefestigungen GmbH, In der Stockwiese 35, 57334 Bad Laasphe
- 5.) Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) :
not relevant
- 6.) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 2+
- 7.) In case of the declaration of performance concerning a construction product covered by a harmonized standard:
not relevant
- 8.) In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
DIBt, Deutsches Institut für Bautechnik issued European Technical Assessment ETA-15/0231 on the basis of ETAG 020. The notified body MPA Stuttgart, Otto-Graf-Institut NB 0672 performed third party tasks under system 2+ and issued the certificate of factory production control number 0672-CPR-0568.

9.) Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Charakteristische Festigkeitswerte	see ETA-15/0231 annex C1, table C1 annex C1, table C2 annex C2, table C4	ETAG 020: 2012
Minimale Bauteildicke, Rand- und Achsabstand in Beton und Mauerwerk	see ETA-15/0231 annex B2, table B2 annex B3, table B3	ETAG 020: 2012
Verschiebung unter Zug- und Querlast in Beton und Mauerwerk	see ETA-15/0231 annex C1, table C3	ETAG 020: 2012

- 10.) The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Frank Dratschmidt / management
 (name and function)

Bad Laasphe, den 09.11.2015
 (place and date of issue)


 (signature)