

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 1050.250

Date : Oct 29, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure – WM 1050.250 - WM202008NC

created : 29.10.2015 build on www.rittal.com/us-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert
Packaging unit:	1 pc(s).
EAN:	4028177532694

Product features

Dimensions:	Height: 500 mm (20 ") Width: 500 mm (20 ") Depth: 210 mm (8.3 ")
Material thickness:	Housing: 1.5 mm (0.06 ")

Door: 1.5 mm (0.06 ")

Mounting plate: Height: 470 mm (19 ")
Width: 449 mm (18 ")

Weight/pack: 17 kg (37.5 lb.)

Approvals

Approvals:  [UL \(EN\)](#)

Downloads

Data sheets: [Graphics \(US\)](#)

Documentation:  [Info sheet \(US\)](#)
 [Load brochure \(US\)](#)

CAD drawings: [Request](#)
