

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.549

Date : Oct 29, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure – WM 8017.549 - WM243008NC

created : 29.10.2015 build on www.rittal.com/us-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert
Packaging unit:	1 pc(s).

Product features

Dimensions:	Height: 600 mm (24 ") Width: 760 mm (30 ") Depth: 210 mm (8.3 ")
Material thickness:	Housing: 1.5 mm (0.06 ") Door: 2 mm (0.08 ")

Mounting plate: Height: 570 mm (22 ")
Width: 704 mm (28 ")


Weight/pack: 32 kg (70.5 lb.)

Approvals

Approvals:  [UL \(EN\)](#)

Downloads

Data sheets: [Graphics \(US\)](#)

Documentation:  [Info sheet \(US\)](#)
 [Load brochure \(US\)](#)

CAD drawings: [Request](#)