

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.588

Date : Oct 29, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure – WM 8017.588 - WM483612NC

created : 29.10.2015 build on www.rittal.com/us-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes 3-point latching L-Handle
Packaging unit:	1 pc(s).

Product features

Dimensions:	Height: 1200 mm (47 ") Width: 900 mm (35 ") Depth: 300 mm (12 ")
Mounting plate:	Height: 1155 mm (45 ") Width: 840 mm (33 ")

3-point locking system:


yes

Weight/pack:

82 kg (180.8 lb.)

Approvals

Approvals:



 [UL \(EN\)](#)

Downloads

Data sheets:

[Graphics \(US\)](#)

Documentation:

 [Info sheet \(US\)](#)
 [Load brochure \(US\)](#)

CAD drawings:

[Request](#)