

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 1034.250

Date : Oct 29, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure – WM 1034.250 - WM161208NC

created : 29.10.2015 build on www.rittal.com/us-en



Product description

| | |
|--|--|
| Material: | Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel |
| Surface finish: | Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated |
| Color: | RAL 7035 |
| Protection category IP to IEC 60 529: | IP 66 |
| Protection category NEMA: | NEMA 4 |
| Supply includes: | Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert |
| Packaging unit: | 1 pc(s). |
| EAN: | 4028177532670 |

Product features

| | |
|----------------------------|--|
| Dimensions: | Height: 400 mm (16 ") Width: 300 mm (12 ") Depth: 210 mm (8.3 ") |
| Material thickness: | Housing: 1.5 mm (0.06 ") |

Door: 1.5 mm (0.06 ")

Mounting plate: Height: 375 mm (15 ")
Width: 254 mm (10 ")

Weight/pack: 9 kg (19.8 lb.)

Approvals

Approvals:  [UL \(EN\)](#)

Downloads

Data sheets: [Graphics \(US\)](#)

Documentation:  [Info sheet \(US\)](#)
 [Load brochure \(US\)](#)

CAD drawings: [Request](#)
