

AC-DC Selector Guide

5-15 Watts	20-40 Watts	45-70 Watts	80-120 Watts	125-150 Watts	175-225 Watts	250-300 Watts	350-400 Watts	500-800 Watts	1000-3000 Watts	DIN Rail	Configurable
 ECE05 • 5 Watts • 1.00" x 1.00" x 0.60" • Class II • PCB Mount • Encapsulated	 ECE20 • 20 Watts • 2.06" x 1.07" x 0.91" • Class II • PCB Mount • Encapsulated	 ECS45 • 45 Watts • 3.00" x 2.00" x 1.05" • Low Leakage Current • <0.3W Standby Power • Class I & II	 ECE80 • 80 Watts • 3.60" x 1.80" x 1.10" • Class II • PCB & Chassis Mount • DIN Rail Option	 CLC125 • 125 Watts • 4.00" x 2.00" x 1.25" • Single Output • Fan Output • Low profile	 RCL175 • 175 Watts • 5.50" x 3.70" x 1.28" • Single & Multi Outputs • Class I & II • Mechanical Options	 CHD250 • 250 Watts • 5.00" x 3.00" x 1.43" • Medical BF Compliant • Convection-cooled • 5V Standby (optional)	 GCS350 • 350 Watts • 5.00" x 3.00" x 1.42" • High Efficiency • Fan Cover Options • Remote On/Off	 GSP500 • 500 Watts • 6.00" x 4.00" x 1.65" • <0.5W Standby Power • Remote On/Off • 5V/2A Standby	 SHP1000 • 1000 Watts • 9.55" x 5.90" x 2.40" • Single Output • Remote On/Off • 1200W High Line	 DNR05-60 • 5 - 60 Watts • Up to 89% Efficiency • Full Power to +60 °C • ANSI/ISA 12.12.01 • DC Standby Versions	 nanoflex • 850 - 1200 Watts • Low 1U Profile • Programmable Voltage • Programmable Current • I²C Interface
 VCE05 • 5 Watts • 1.30" x 1.10" x 0.75" • PCB Mount • Class II • Low Cost	 ECS25 • 25 Watts • 4.35" x 2.00" x 0.95" • Single Output • <0.3W Standby Power • Class I & II	 VCS50 • 50 Watts • 4.35" x 3.07" x 1.38" • Single Output • Convection-cooled • Low Cost	 ECS100 • 100 Watts • 4.00" x 2.00" x 1.25" • Low Profile • <0.5W Standby Power • Class I & II	 ECS130 • 130 Watts • 4.00" x 2.00" x 1.25" • Class I & II • High Efficiency • 100W Convection-cooled	 ECP180 • 180 Watts • 4.00" x 2.00" x 1.00" • Single Output • 120W Convection-cooled • Up to 95% Efficiency	 CCB250/CCM250 • 250 Watts • 6.00" x 4.00" x 1.50" • Single Output • Convection-cooled • Up to 95% Efficiency	 EMH350 • 350 Watts • Medical BF Compliant • Single & Dual Outputs • Optional Oring Diode • Analog & PMBus Options	 SMH600 • 600 Watts • 8.00" x 5.00" x 1.60" • Single & Dual Outputs • Up to 900W Peak Power • Remote On/Off	 MHP1000 • 1000 Watts • 9.55" x 5.90" x 2.40" • Single Output • Remote On/Off • 1200W High Line	 DNR120-480 • 120 - 480 Watts • Up to 90% Efficiency • Full Power to +60 °C • ANSI/ISA 12.12.01 • DC Standby Versions	 flexPower X & XM4,5&7 • 400 - 900 Watts • 10.00" x 5.00" x 2.50" • 1 - 10 Outputs • SEMI F47 Compliant • Fan Speed Control
 EME05 • 5 Watts • 1.00" x 1.5" x 0.60" • Class II • PCB Mount • Encapsulated	 ECL25/30 • 25/30 Watts • 2.96" x 1.36" x 1.05" • Single & Multi Outputs • PCB & Chassis Mount • Class II	 ECS60 • 60 Watts • 3.00" x 2.00" x 1.05" • Low Leakage Current • <0.5W Standby Power • Class I & II	 ECM100 • 100 Watts • 4.50" x 2.50" x 1.20" • Single & Multi Outputs • Class I & II • PoE Version	 ECP130 • 130 Watts • 3.00" x 2.00" x 1.10" • 100W Convection-cooled • Up to 95% Efficiency • Low Profile	 GCS180 • 180 Watts • 5.00" x 3.00" x 1.42" • Class I & II • Remote On/Off • 150W Convection-cooled	 GCS250 • 250 Watts • 5.00" x 3.00" x 1.42" • Class I & II • Remote On/Off • 180W Convection-cooled	 SHP350 • 350 Watts • 7.06" x 3.60" x 2.10" • Single Output • Remote On/Off • 5V Standby	 CCH600 • 600 Watts • 8.43" x 4.02" x 1.69" • Single Output • Baseplate-cooled • Industrial & MIL-STD	 HCP1000 • 1000 Watts • 11.14" x 5.00" x 1.61" • Programmable Voltage • Programmable Current • Controls and Alarms	 DSA150-480 • 150 - 480 Watts • Up to 94% Efficiency • Ultra Slim Design • 150% Peak Load • Redundancy Module	 flexPower X & XM9 • 900 - 1100 Watts • 10.00" x 6.00" x 2.50" • 1 - 12 Outputs • SEMI F47 Compliant • Fan Speed Control
 ECL05/10 • 5/10 Watts • 2.00" x 1.00" x 0.90" • Single Output • PCB & Chassis Mount • Class II	 EML30 • 30 Watts • 2.96" x 1.36" x 1.05" • Single Output • PCB & Chassis Mount • Class II	 ECP60 • 60 Watts • 4.00" x 2.00" x 1.20" • Single & Multi Outputs • Low Profile • Peak Load Capacity	 VCS100 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Low Cost	 ECP150 • 150 Watts • 4.00" x 2.00" x 1.26" • Single Output • 100W Convection-cooled • Up to 92% Efficiency	 CCB200 • 200 Watts • 5.00" x 3.00" x 1.43" • Full Power to +70 °C • Convection-cooled • Up to 95% Efficiency	 EMH250 • 250 Watts • 5.00" x 3.00" x 1.43" • Single Output • Medical BF Compliant • 80-275 VAC Operation	 CCL400 • 400 Watts • 7.00" x 3.95" x 1.57" • Convection-cooled • 94% Efficiency • 5V Standby	 SHP650/MHP650 • 650 Watts • 9.81" x 4.00" x 2.50" • Single Output • Remote On/Off • Mechanical Options	 GFR1K5 • 1500 Watts • 11.80" x 4.00" x 1.70" • 1U Hot Swap • I²C Interface • Current Share & Signals	 DNR120-960 • 120 - 960 Watts • Up to 93% Efficiency • Full Power to +60 °C • Three Phase Input • ANSI/ISA 12.12.01	 flexPower X & XM10 • 1000 - 1200 Watts • 10.00" x 7.00" x 2.50" • 1 - 14 Outputs • SEMI F47 Compliant • Fan Speed Control
 ECE10 • 10 Watts • 1.00" x 1.45" x 0.60" • Class II • PCB Mount • Encapsulated	 ECE40 • 40 Watts • 3.10" x 1.50" x 1.10" • Class II • PCB & Chassis Mount • DIN Rail Option	 ECE60 • 60 Watts • 3.60" x 1.50" x 1.10" • Class II • PCB & Chassis Mount • DIN Rail Option	 ECC100 • 100 Watts • 5.00" x 4.10" x 1.78" • Single Output • Baseplate-cooled • Remote On/Off	 GCS150 • 150 Watts • 5.00" x 3.00" x 1.42" • High Efficiency • Class I & II • 110W Convection-cooled	 EPL225 • 225 Watts • 4.00" x 2.0" x 1.26" • Single Output • 12V Fan Outputs • Up to 95% Efficiency	 CMH250 • 250 Watts • 7.00" x 4.00" x 1.57" • Single Outputs • 5V/1.5A Standby • Convection-cooled	 CCH400 • 400 Watts • 8.43" x 4.02" x 1.69" • Single Output • Baseplate-cooled • Industrial & MIL-STD	 HCP650 • 650 Watts • 9.80" x 5.00" x 1.61" • Programmable Voltage • Programmable Current • Controls and Alarms	 HPU1K5/HPD1K5 • 1500 Watts • 12.75" x 4.00" x 1.70" • Low Profile • Current Share • Programmable Voltage	 flexPower X & XM15 • 1500 - 2500 Watts • 11.00" x 5.00" x 5.00" • 1 - 20 Outputs • SEMI F47 Compliant • Fan Speed Control	
 ECL15 • 15 Watts • 2.44" x 1.21" x 0.95" • Single & Multi Outputs • PCB & Chassis Mount • Class II	 ECM40 • 40 Watts • 4.00" x 2.00" x 1.20" • Single & Multi Outputs • Class I & II • Low Leakage Current	 ECS65 • 65 Watts • 4.00" x 2.00" x 1.05" • Class I & II • <0.5W Standby Power • Low Leakage Current	 ASB110 • 110 Watts • 4.40" x 2.40" x 0.67" • Single Output • Baseplate-cooled • Universal Input	 LCL150 • 150 Watts • 7.55" x 3.74" x 1.97" • Single Output • Convection-cooled • Low Cost	 ECP225-A • 225 Watts • 5.00" x 3.00" x 1.00" • 5V/2A Standby • Fan Supply • Up to 95% Efficiency	 GCS265 • 265 Watts • 5.00" x 3.50" x 1.43" • High Efficiency • 5V/3A Standby • Class I & II	 FCM400 • 400 Watts • 6.00" x 4.00" x 1.93" • Single Output • Low Noise Fan • 5V Standby	 HHP650 • 650 Watts • 9.99" x 4.20" x 2.50" • Conformal Coating • SEMI F47 Compliant • 6kV Surge Rating	 HDS1500/3000 • 1500/3000 Watts • Controls and Alarms • Programmable Voltage • Programmable Current • I²C Interface	 flexPower XT16 • 1600 Watts • 11.00" x 7.00" x 2.50" • 1 - 14 Outputs • Three Phase Input • Fan Speed Control	
 EML15 • 15 Watts • 2.44" x 1.21" x 0.95" • Single Output • PCB & Chassis Mount • Class II	 ECP40 • 40 Watts • 3.00" x 2.00" x 0.90" • Single & Multi Outputs • Class I • Low Profile	 VCS70 • 70 Watts • 5.12" x 3.88" x 1.61" • Single Output • Convection-cooled • Low Cost			 UCP225 • 225 Watts • 3.12" x 5.00" x 1.18" • 5V Standby • Fan Supply • 150W Convection-cooled	 LCL300 • 300 Watts • 8.07" x 4.33" x 1.97" • Single Output • Remote On/Off • Low Cost	 SDL400 • 400 Watts • 6.00" x 4.00" x 1.50" • Single & Dual Outputs • Low Leakage Current Opt. • Up to 700W Peak Power	 HDS800 • 800 Watts • 9.80" x 5.00" x 1.61" • Programmable Voltage • Programmable Current • Controls and Alarms	 HDL3000 • 3000 Watts • 12.48" x 6.69" x 2.50" • Programmable Voltage • Programmable Current • Parallel Operation		



= Green Product



= Medical Version Available

For full specifications visit: www.xppower.com

5-8 Watts	10-15 Watts	18-30 Watts	36-40 Watts	45-60 Watts	65-70 Watts	80-90 Watts	100 Watts	120 Watts	150 Watts	180 Watts	220-250 Watts
   VER05 • 5 Watts • Level VI & CoC Tier 2 • 1.45" x 2.16" x 1.69" • Changeable Input Plugs • Class II Construction	   VEL12 • 12 Watts • Level VI & CoC Tier 2 • 2.99" x 1.95" x 1.83" • Class II Construction • Low Cost	   VEL18 • 18 Watts • Level VI & CoC Tier 2 • 2.99" x 1.95" x 1.83" • Class II Construction • Low Cost	   AEJ36 • 36 Watts • Level VI & CoC Tier 2 • 4.37" x 2.01" x 0.78" • Low Profile • Class II Construction	   AFM45 • 45 Watts • Energy Efficiency Level V • 4.76" x 1.97" x 1.21" • Class I & II Versions • Optional White Case	   ALM65 • 65 Watts • Energy Efficiency Level VI • 4.94" x 2.19" x 1.32" • Class I & II Versions • IP32 Rating	   AHM85 • 85 Watts • Energy Efficiency Level V • 5.90" x 2.52" x 1.45" • IP22 Rating • Class I & II Versions	   AEJ100 • 100 Watts • Level VI • CoC Tier 2 • 5.59" x 2.28" x 1.48" • Wide Output Range	   VES120 • 120 Watts • Level VI & CoC Tier 2 • 6.61" x 2.80" x 1.48" • CCC Qualified • Low Cost	   AHM150 • 150 Watts • Energy Efficiency Level V • 7.80" x 3.15" x 1.45" • IP22 Rating • Class I & II Versions	   AHM180 • 180 Watts • Energy Efficiency Level V • 7.87" x 3.15" x 1.61" • IP22 Rating • Class I & II Versions	   AHE220 • 220 Watts • Energy Efficiency Level VI • 7.76" x 3.46" x 1.73" • High Power Density • <0.21 W Standby Power
   VEL05 • 5 Watts • Level VI & CoC Tier 2 • 1.40" x 2.17" x 0.95" • Class II Construction • Low Cost	   VER12 • 12 Watts • Level VI & CoC Tier 2 • 3.01" x 1.61" x 1.48" • Changeable Input Plugs • Class II Construction	   VER18 • 18 Watts • Level VI & CoC Tier 2 • 3.01" x 1.61" x 1.48" • Changeable Input Plugs • Class II Construction	   VEL36 • 36 Watts • Level VI & CoC Tier 2 • 3.70" x 1.38" x 1.83" • Class II Construction • Low Cost	   AEJ50 • 50 Watts • Level VI • CoC Tier 2 • 4.72" x 2.05" x 1.22" • Full Power to 50 °C	   VEC65 • 65 Watts • Level VI & CoC Tier 2 • 4.58" x 2.06" x 1.23" • CCC Qualified • LPS Approved	   AJM90 • 90 Watts • Energy Efficiency Level VI • 5.51" x 2.80" x 0.87" • Class I and II Versions • Very Low Profile	   AHM100 • 100 Watts • Energy Efficiency Level V • 6.49" x 2.52" x 1.45" • IP22 Rating • Class I & II Versions				
   ACM06 • 6 Watts • Level VI & CoC Tier 2 • 2.89" x 1.67" x 1.21" • Changeable Input Plugs • Class II Construction	   VEP15 • 15 Watts • Energy Efficiency Level V • 2.95" x 1.20" x 1.81" • Changeable Input Plugs • Class II Construction	   VEL24 • 24 Watts • Level VI & CoC Tier 2 • 3.54" x 1.95" x 1.96" • Class II Construction • Low Cost	   VER36 • 36 Watts • Level VI & CoC Tier 2 • 3.72" x 1.85" x 1.71" • Class II Construction • Low Cost	   VEC50 • 50 Watts • Level VI & CoC Tier 2 • 4.58" x 2.06" x 1.23" • CCC Qualified • LPS Approved	   AEJ70 • 70 Watts • Level VI • CoC Tier 2 • 4.72" x 2.01" x 1.22" • Full Power to 50 °C	   VES90 • 90 Watts • Level VI & CoC Tier 2 • 5.47" x 2.28" x 1.22" • CCC Qualified • Low Cost					
   VEP08 • 8 Watts • Energy Efficiency Level V • 1.06" x 2.83" x 1.67" • Class II Construction • Changeable Input Plugs	   ACM18 • 18 Watts • Level VI & CoC Tier 2 • 3.46" x 1.18" x 1.95" • Changeable Input Plugs • Class II Construction	   VEP24 • 24 Watts • Energy Efficiency Level IV • 3.46" x 1.14" x 1.89" • Changeable Input Plugs • Class II Construction	   VEC40 • 40 Watts • Level VI & CoC Tier 2 • 4.58" x 2.06" x 1.23" • CCC Qualified • LPS Approved	   AFM60 • 60 Watts • Energy Efficiency Level V • 4.92" x 2.44" x 1.33" • Class I & II Versions • Optional White Case							
		   VER24 • 24 Watts • Level VI & CoC Tier 2 • 3.54" x 1.69" x 1.68" • Class II Construction • Changeable Input Plugs									
		   AFM30 • 30 Watts • Energy Efficiency Level V • 4.76" x 1.97" x 1.21" • Class I & II Versions • Optional White Case									

Next generation,
ultra-high
efficiency designs

Board level
environmental
committee

ISO 14001

Leader in
environmental
manufacturing

Member of
Electronic Industry
Citizenship
Coalition (EICC)



