



5551L 4K 54.6-inch UHD

Touchscreen Signage



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 5551L 54.6" Ultra High Definition (UHD) touchscreen signage display features phenomenal 4K resolution image quality. With a 10-touch 'tablet-like' performance, the infrared touchscreen technology provides higher touch sensitivity and brightness in a large 54.6" size. The 5551L delivers undistorted display clarity due to use of clear glass with three key features:

- True native 4K resolution at 60 Hz (with DisplayPort)
- Auto-switching between active input sources eases use in meeting rooms
- RS232C serial control input

Optional, high performance computer modules are available which turn the 5551L into a all-in-one computer—without the need for any cables or additional mounting hardware.

State of the art full UHD display and video technology

Thin (<4" mounted) design is attractive and compliant with ADA and IBC protrusion requirements

Flexible mounting in portrait, landscape and table-top orientation

5551L 4K 54.6-inch UHD Touchscreen Signage

| Specifications | |
|---------------------------------------|--|
| Model | 5551L 4K |
| Form Factor | Digital Signage |
| Bezel Color | Black |
| Active Display Area (W x H) | 47.6" x 26.8" (1209.6mm x 680.4mm) |
| Dimensions (W x D x H) | 49.8" x 29.0" x 3.5" (1267mm x 738mm x 90mm) |
| Mounting Options | VESA 4-hole mount per MIS-F, 600, 600, 6MM |
| Display Technology | Full HD 3840 x 2160 60Hz (native) active matrix TFT LCD with LED backlight |
| Aspect Ratio | 16:9 |
| Number of Colors | 1073.7 million |
| Brightness (typical) | LCD Panel 450 nits; with Infrared 405 nits |
| Response Time (Tr + Tf) (typical) | 6.5 msec |
| Viewing Angle (typical) | Horizontal: ±89°/178° total; Vertical: ±89°/178° total |
| Contrast Ratio (typical) | 4000:1 |
| On-Screen Display (OSD) | Accessible through switches on the unit's tethered OSD Control box. Controls: Menu, Up, Down, Select, Power; Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Source; OSD Timer: Change between 5 and 60 seconds; Color Adjust: 9300K, 7500K, 6500K, 5500K and User mode; Color Preference: Standard, Gaming, Movie, Photo, Webcam, Blur; Saturation and Hue: In any mode other than Standard mode; Audio: From Video Source, From Line-in and ECM Line-in; Audio Controls: Mute, Volume Up and Down; Video: Choose from VGA, HDMI, DisplayPort, Computer Module HDMI or DisplayPort; MDC Protocol: IIC or RS232; Black Level: Standard, 5%, 10% and 20% Offset; Light Sensor; Sharpness Level; Aspect Ratio: Fill Screen, Fill to Aspect Ratio and Direct Output; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power; Other Settings: Power Behavior, Tabletop mode, Information, MDC Protocol, Support and Help, System Temperature and Exit |
| Video Inputs | HDCP-capable HDMI on Type A connector; DisplayPort 1.1a connector; Input Video Horizontal Sync frequency range: 30 - 139.2 KHz; Input Video Vertical Sync (frame rate) frequency range: 24 - 63 Hz |
| Power | Input power connector: IEC 60320 C14; Input power signal specifications: 100-240VAC 50/60Hz Monitor Only - Power Consumption: (typical at 120V at 60Hz): ON: 157W; SLEEP: 15W; OFF: 0.7W Monitor Only - Power Consumption: (typical at 230V at 50Hz): ON: 156W; SLEEP: 15W; OFF: 0.8W |
| Audio | Internal Speakers: 4 x 5W stereo speakers; Input audio connector: 3.5mm TRS jack; Input audio signal range: 1Vrms max stereo signal (standard PC line out); Headphone output connector: 3.5mm TRS jack |
| Weight | Unpackaged with ECMG2B: 105 lbs (47.6 kg); without ECMG2B: 100 lbs (45.4 kg) Packaged with ECMG2B: 126 lbs (57.2 kg); without ECMG2B: 121 lbs (55 kg) |
| Shipping Dimensions | 56" x 35" x 9.3" (1420mm x 880mm x 235mm) |
| Temperature | Portrait/Landscape Mode - Operating: 0° C to 40° C (32° F to 104° F); Storage: -20° C to 50° C (-4° F to 122° F); Tabletop Mode - Operating: 0° C to 35° C (32° F to 95° F); Storage: -20° C to 50° C (-4° F to 122° F); With OPS module - Operating: 0° C to 35° C (32° F to 95° F); Storage: -20° C to 50° C (-4° F to 122° F) |
| Humidity (non-condensing) | Operating: 20%-80%; Storage: 10%-95% |
| Regulatory Approvals and Declarations | UL, FCC; cUL, IC; CB; CE |
| Accessories | NFC Adapter (E918074), OPS Kit (E102270), OSD Control Box (E483757) Replacement Cable Kit (E000263), Wall Mount Kit (E248743), Webcam (E688656) |
| RFID Supported Protocols | ISO - 14443-A; ISO - 14443-B; ISO - 15693 |
| Warranty | 3 year standard (worldwide) with on-site exchange (NA only). 2 year extended warranty option available (NA and EMEA only). |
| MTBF | 50,000 hours demonstrated |
| What's in the box | QIG, JP Class A Kiosk Info, HDMI cable, DisplayPort cable, USB cable, RS232 cable, 3.5mm audio cable, power cable (NA, EU/ KR, UK, AR, CH, and JP plugs), 3-pin to 2-pin adapter for JP power cable, Energy label according to EU Regulation 1062/2010 |

Ordering Information

| Model | Part Number | Technology | Surface Treatment | Touch Interface | Availability |
|----------|-------------|------------|-------------------|-----------------|--------------|
| 5551L 4K | E268447 | Infrared | Clear | USB | Worldwide |

Optional Computer Modules

| Model | Part Number | Processor | RAM | HDD | OS |
|-----------|-------------|--|-----|-------|-------------|
| ECMG2B-i3 | E001292 | Intel® Core™ 4th Gen i3 3.4 GHz HD4400 | 2GB | 320GB | No OS |
| | E001293 | Intel Core 4th Gen i3 3.4 GHz HD4400 | 2GB | 320GB | Windows 7 |
| | E001294 | Intel Core 4th Gen i3 3.4 GHz HD4400 | 2GB | 320GB | Windows 8.1 |
| | E991018 | Intel Core 4th Gen i3 3.4 GHz HD4400 | 2GB | 128GB | Windows 10 |
| ECMG2B-i5 | E001295 | Intel Core 4th Gen i5 3.7 GHz HD4600 | 4GB | 320GB | No OS |
| | E001296 | Intel Core 4th Gen i5 3.7 GHz HD4600 | 4GB | 320GB | Windows 7 |
| | E001297 | Intel Core 4th Gen i5 3.7 GHz HD4600 | 4GB | 320GB | Windows 8.1 |
| | E991722 | Intel Core 4th Gen i5 3.7 GHz HD4600 | 4GB | 128GB | Windows 10 |
| ECMG2B-i7 | E001298 | Intel Core 4th Gen i7 4.0 GHz HD4600 | 8GB | 320GB | No OS |
| | E001299 | Intel Core 4th Gen i7 4.0 GHz HD4600 | 8GB | 320GB | Windows 7 |
| | E001300 | Intel Core 4th Gen i7 4.0 GHz HD4600 | 8GB | 320GB | Windows 8.1 |
| | E992193 | Intel Core 4th Gen i7 4.0 GHz HD4600 | 8GB | 128GB | Windows 10 |

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
Fax +1 408 597 8050
elosales.na@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +1 786-923-0251
Fax +1 305-931-0124
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17013AES00017

