

1.27mm Pin Header & Board Spacer
 1.27mm x 2.54mm Board Spacer



SL 1

SPECIFICATIONS

Current rating	1 A
Insulator resistance	5000 MΩ min.
Contact resistance	20 mΩ max.
Dielectric withstanding voltage	500 V AC
Operating temperature	- 40° to +105°C
Processing temperature SL1 & SL2	+250°C +0/-5°C for 20sec.
Processing temperature SP1 & SP2	+250°C +0/-5°C for 5sec.
Contact material (RoHS compliant)	Copper alloy
Insulator material (RoHS compliant)	Nylon, UL 94 V-0

SP 1

PCB Hole Layout

How to order

S xx - xxx - S xxx/xx - 55 /1

Single plastic	Nbr of contacts	Terminal code & dimensions	Plating																
L1 = single row L2 = dual row	single row = 003 to 050 dual row = 006 to 100	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Code</th> <th>A</th> <th>B</th> </tr> </thead> <tbody> <tr> <td>079 / 01</td> <td>2.80 mm</td> <td>2.60 mm</td> </tr> <tr> <td>111 / 01</td> <td>6.00 mm</td> <td>2.60 mm</td> </tr> <tr> <td colspan="3" style="text-align: center;">Other dimensions on request</td> </tr> </tbody> </table>	Code	A	B	079 / 01	2.80 mm	2.60 mm	111 / 01	6.00 mm	2.60 mm	Other dimensions on request			55 = gold Other platings on request				
Code	A	B																	
079 / 01	2.80 mm	2.60 mm																	
111 / 01	6.00 mm	2.60 mm																	
Other dimensions on request																			
Double plastic "Boardspacer"	Nbr of contacts	Terminal code & dimensions	Plating																
P1 = single row P2 = dual row	single row = 003 to 050 dual row = 006 to 100	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Code</th> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>116 / 01</td> <td>2.80 mm</td> <td>2.60 mm</td> <td>6.20 mm</td> </tr> <tr> <td>152 / 01</td> <td>6.00 mm</td> <td>3.00 mm</td> <td>6.20 mm</td> </tr> <tr> <td colspan="4" style="text-align: center;">Other dimensions on request</td> </tr> </tbody> </table>	Code	A	B	C	116 / 01	2.80 mm	2.60 mm	6.20 mm	152 / 01	6.00 mm	3.00 mm	6.20 mm	Other dimensions on request				55 = gold Other platings on request
Code	A	B	C																
116 / 01	2.80 mm	2.60 mm	6.20 mm																
152 / 01	6.00 mm	3.00 mm	6.20 mm																
Other dimensions on request																			