


REV	DESCRIPTION	DATE	BY
A	NEW DRAWING	02/09/06	H.N.
B	ADDED TOLERANCES	10/29/07	JAG
C	UPDATED DRAWING	07/11/14	JAG

SKT2543

TOP



BOTTOM


Pointing Accuracy: ± 0.05 mm

Spring Force: ± 20%

STATE	TRAVEL	SPRING FORCE
Initial Travel	--	12.5g (0.441oz)
Recommended Travel	0.8mm (0.0315)	31.3g (1.104oz)
Full Travel	1.1mm (0.0433)	38.3g (1.351oz)

PART	MATERIAL	FINISH
Top Plunger	Hardened Steel	Gold Plated
Bottom Plunger	Hardened Steel	Gold Plated
Barrel	Phosphor Bronze	Gold Plated
Spring	Stainless Steel	Gold Plated

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED

	EMULATION TECHNOLOGY, INC. VLSI and SMT ADAPTERS and ACCESSORIES	
	759 FLYNN ROAD CAMARILLO, CA 93012	TEL: (805) 383-8480 FAX: (805) 383-8484
SHEET: 1 OF 1	DATE: 02/09/06	REVISION: C
ASSEMBLY DRAWING		
CHECKED: Perry Munroe	PREPARED BY: Huy Nguyen	ITEM: POGO-PIN-8.69-2
DO NOT SCALE DRAWING		DESCRIPTION: POGO-PIN-8.69-2