


<b>PROPRIETARY INFORMATION:</b> PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY			
H	ADD ROHS, RFS. 9522, FS	10/13/06	BS
I	CHANGE BS1363A REQUIREMENT TO 10A., RFS. 9577, BS	10/20/06	BS
J	CORRECT P/N TO PZ0800100-2M5BK13H(R), RFS. 14715, BS	10/01/08	BS
K	UPDATE APPROVALS ,RFS. 20122, BS	12/13/10	BS
L	UPDATE ASTA LICENSE # FROM 775 TO 839 ,RFS. 22330, BS	02/02/12	BS


REVISION			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	09/19/02	BS
B	REVISED CABLE NOTES	01/13/03	BS
C	PLUG APPROVALS CORRECTION	02/07/03	BS
D	PLUG & CONNECTOR APPROVALS CORRECTION	04/07/03	BS
E	CORRECTION TITLE	08/19/03	BS
G	REMOVE NOTES, RFS.4253, BS	08/09/04	BS



### GENERAL SPECIFICATIONS:


RATING: 10A / 250 V AC  
 CABLE TYPE / SIZE: H05VV-F, 3 X 1 mm<sup>2</sup>  
 TEMPERATURE RATING: 70° C  
 CONDUCTOR COLORS: BLUE / BROWN / GREEN/YELLOW  
 CABLE JACKET COLOR: BLACK  
 OVERALL LENGTH (L): 2500 ± 20 mm  
 CABLE OUTER DIAMETER: 7.1 ± 0.2 mm  
 END 'A' TERMINATION: BS 1363A, FUSED AT 10A  
 END 'B' TERMINATION: IEC 320 /C13 (BS 4491)  
 APPROVALS PLUG: ASTA +SINGAPORE + HONG KONG  
 APPROVALS CONNECTOR: VDE, N, S, D, FI, KEMA, SEV, CEPEC, OVE, IMQ, ASTA  
 APPROVALS CABLE: VDE, N, S, D, FI, KEMA, SEV, CEPEC, OVE, IMQ

### PACKING: HANKING



### NOTES:

1. PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).
2. CONNECTOR APPROVALS FOR EUROPE WILL BE REPLACED BY A SINGLE ENEC MARK IN 2011.

DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
<b>TABULATION BLOCK</b>				
		<b>TOLERANCES:</b> DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005		 <b>GlobTek, Inc.</b> www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111
		<b>MILLIMETERS ANGULAR</b> .xx +/- 0.3 +/- 1° .xxx +/- .013		
INIT.BY:	DATE:	<b>DWG TITLE: BRITISH DETACHABLE CORDSET</b>		
DRAWN: NF	DATE:	FSCN No.:	SIZE	MODEL: N / A
APRVD: BS	DATE:	SCALE: NONE	PART NO: <b>PZ0800100-2M5BK13H(R)</b>	REV. L
				SHEET 1/1



Foot Note:  
Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:  
Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice