



FTxx\*1)S1Gy\*2)  
e.g. FT09S1G1

\*1) xx No. of contacts 09, 15, 25 or 37  
\*2) y for performance classes 1, 2 or 3  
(contact cycle for G1/G2/G3 = 500/200/50)

xx	A [mm]	B [mm]	C [mm]	*E [mm]
09	30.8	16.4	25	ø1
15	39.1	24.7	33.3	
25	53	38.5	47.04	
37	69.3	54.9	63.5	

\*PCB hole patterns, øE on supplement AM0023

RoHS compliant

No.	St.	Part	Type	Description/Material	Surface plating/Colour/Class
4	2	Clinch nut	FT 4-40	Steel	tin plated
3	xx	Signal contact	S1	Brass	G1/G2/G3
2	1	Shell		Steel	tin plated
1	1	Insulator		PBT (-55°C - +125°C)	white

	Measurement without tolerance occ. to ISO 2768-m	SCALE	TITLE
		2:1	
	NAME / DATE		
DRAWN	schref		D-Sub Miniature Connector
CHECKED	dittel		
	12-07-2002		
	12-07-2002		



DWG.NO.	FTxxS1Gy	REV.	1
REPLACEMENT FOR:		PAGES	1

COMMENT: ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING. WITHOUT OUR PRIOR CONSENT, IT MAY NEITHER BE DUPLICATED NOR MADE AVAILABLE TO A THIRD PARTY. AND IT ALSO MAY NOT BE IMPROPERLY USED BY THE RECEIVER, OR A THIRD PARTY.