



ISO 9001:2000	DIMENSIONS				LOAD RATING		WT.
Part Number	d	D	B	C	Dynamic Cr (N)	Static Cor (N)	lbs
inch							
<b>LIGHT 200 SERIES, R-SEAL, NON-RELUBRICATABLE TYPE, CYLINDRICAL O.D., ROUND BORE</b>							
203KRR5	0.5150		0.7200				
203KR2	0.6253	1.5748	0.5510	0.4720	1060	2450	0.5640
203KRR2	0.6400		0.7200				
203KRR7	0.6693		0.6540				
204KR2	0.7505	1.7805	0.6100	0.6100	1460	3250	0.7810
204KRR3	0.7874	1.8504	0.6990	0.5510	1460	3250	0.7810
205KR4	1.0005	2.0472	1.0000	0.5910	1760	3600	0.8790
206KR7	1.1811	2.4409	0.9450	0.6300	2550	4900	1.2700
206KRR8							1.3200
207KRR	1.3780	2.8346	0.9840	0.6690	3450	6550	1.7200
208KRR2	1.5748	3.1496	1.0630	0.8270	4500	8300	2.2500
209KRR3	1.7717	3.3465					
210KRR	1.9685	3.5433	1.1810	0.7870	5200	9000	2.5000
212KRR	2.3622	4.3307	1.4170	0.8860	8000	13200	3.9100

**FIT STRIVES FOR 100% IN ON-TIME DELIVERIES**