


ZZ

2RS


ISO 9001:2000	DIMENSIONS				LOAD RATING		LIMITING SPEED		WT.
Part Number	d	D	W1 (2RS / ZZ)	r (min)	Dynamic Cr (N)	Static Cor (N)	Grease Rpm	Oil Rpm	Open lbs
6800 METRIC SERIES, EXTRA THIN LINE									
6800	10	19	5	0.3	1076	627	36000	43000	0.0160
6801	12	21			1430	670	32000	38000	0.0190
6802	15	24			1560	800	28000	34000	0.0280
6803	17	26			1680	930	24000	30000	0.0320
6804	20	32	7		2700	1500	19000	24000	0.0630
6805	25	37	7	0.3	4360	2600	17000	20000	0.7400
6806	30	42			4490	2900	15000	18000	0.0850
6807	35	47			4750	3200	13000	16000	0.1040
6808	40	52			4940	3450	11000	14000	0.1940
6809	45	58			6050	4300	9500	12000	0.2260
6810	50	65			6240	4750	9000	11000	0.2340
6900 METRIC SERIES, EXTRA THIN LINE									
6900	10	22	6	0.3	1950	750	34000	40000	0.0200
6901	12	24			2250	980	30000	36000	0.0240
6902	15	28			7	4030	2040	24000	30000
6903	17	30	4360	2320		22000	28000	0.0400	
6904	20	37	9		6370	3650	18000	22000	0.0790
6905	25	42	9	0.3	6630	4000	16000	19000	0.0930
6906	30	47			7280	4550	14000	17000	1.0600
6907	35	55	10	0.6	9560	6200	11000	14000	0.1630
6908	40	62	12	0.6	13800	9300	10000	13000	0.2430
6909	45	68			14000	9800	9000	11000	0.2820
6910	50	72			14600	10400	8500	10000	0.2910

FIT'S SHANGHAI QUALITY CONTROL CENTER HAS STATE-OF-THE-ART TESTING EQUIPMENT
CORPORATE - WEST COAST SALES
 47655 Warm Springs Blvd
 Fremont, CA 94539
 Toll Free: (800) 808-0348
 Phone: (510) 623-1688


MIDWEST SALES - DISTRIBUTION
 2800 Galvin Drive
 Elgin, IL 60124
 Toll Free: (877) 808-0348
 Phone: (847) 836-8200



87000
Single Seal and Shield



88000
Double Felt Seal



SNAP RING R

ISO 9001:2000	DIMENSIONS						LOAD RATING		LIMITING SPEED	WT.	
Part Number	d	D	W1	W0	W	r (min)	Dynamic	Static	Grease	Open	
	mm						Cr (N)	Cor (N)	Rpm	lbs	
87000 SERIES, FELT SEALED											
87503	17.00	40	13.665	12	14.290	0.6	2150	1080	12000	0.154	
87504	20.00	47	15.240	14	15.875	1.0	2860	1500	10000	0.237	
87505	25.00	52		15			3150	1770	8500	0.292	
87506	30.00	62	19.000	16	20.000		4390	2540	7500	0.506	
87507	35.00	72	20.000	17	21.000		5740	3450	6300	0.708	
87508	40.00	80	24.000	21	24.000	1.1	6910	4000	5600	0.945	
87509	45.00	85		21			24.000	7470		4570	1.123
87510	50.00	90		26.000			22	26.000	7900	5240	5600
88000 SERIES, FELT SEALED											
88128 88128R	38.98	80	27.511	21	27.510	1.1	6910	4000	5600	1.060	
88503	17.00	40	16.600	12	16.600	0.6	2150	1080	12000	0.176	
88504	20.00	47	17.750	14	17.750	1.0	2860	1500	10000	0.259	
88505	25.00	52		15			16.750	3150	1770	8500	0.304
88506	30.00	62	24.000	16	24.000		1.0	4390	2540	7500	0.571
88507	35.00	72	25.000	17	25.000		1.1	5740	3450	6300	0.765
88508	40.00	80	27.000	21	27.000	1.1	6910	4000	5600	1.180	
88509	45.00	85		21			27.000	7470		4570	1.220
88510	50.00	90	30.000	22	30.000			7900	5240	5600	1.400

CUSTOMERS ARE ALWAYS ENCOURAGED TO VISIT FIT'S SHANGHAI QUALITY CONTROL CENTER