

**ASTM 80 CHAIN**

Nom. Size		Wrk. Load Limit (Max.)	Proof Load (Min.)	Min. Break. Load	Wt. Per 100'	Ins. Length (Max.)	Ins. Width (Min.)
inch	mm	lb.				inch	inch
<b>GRADE 30 (PROOF COIL)</b>							
1/8	4.0	420	850	1700	19	0.89	0.29
3/16	5.5	800	1600	3200	40	0.95	0.40
1/4	7.1	1330	2650	5300	72	1.00	0.50
5/16	8.7	2000	4000	8000	106	1.10	0.50
3/8	10.3	2800	5600	11200	155	1.23	0.62
1/2	13.5	4800	9650	19300	271	1.53	0.80
5/8	16.7	7400	14800	29600	405	1.90	1.00
3/4	19.8	10400	20800	41600	582	2.15	1.12
7/8	23.0	14000	28000	56000	811	2.50	1.37
1	26.5	18600	37200	74400	1045	2.75	1.50
<b>GRADE 43 (HIGH TEST)</b>							
1/4	7.1	2600	4300	7750	80	0.86	0.40
5/16	8.7	3900	6400	11600	111	1.05	0.48
3/8	10.3	5400	8900	16200	160	1.19	0.58
1/2	13.5	9200	15300	27600	284	1.43	0.75
<b>GRADE 70 (TRANSPORT)</b>							
1/4	7.1	3150	6300	12600	75	0.86	0.45
5/16	8.7	4700	9400	18800	111	1.01	0.46
3/8	10.3	6600	13200	26400	156	1.19	0.55

**OTHER TYPES OF CHAIN AVAILABLE**


**NACM 84/90 CHAIN**


Nom. Size		Wrk. Load Limit (Max.)	Proof Load (Min.)	Min. Break. Load	Wt. Per 100'	Ins. Length (Max.)	Ins. Width (Min.)
inch	mm	lb.				inch	inch
<b>GRADE 30 (PROOF COIL)</b>							
1/8	4.0	375	800	1600	19.8	0.94	0.25
3/16	5.5	800	1600	3200	40.3	0.98	0.30
1/4	7.0	1300	2600	5200	66.1	1.24	0.38
5/16	8.0	1900	3400	6800	86.0	1.29	0.44
3/8	10.0	2650	5300	10600	142	1.38	0.55
1/2	13.0	4500	8950	17900	242	1.79	0.72
5/8	16.0	6900	13600	27200	357	2.20	0.79
3/4	20.0	10600	21200	42400	560	2.76	0.98
7/8	22.0	12800	25600	51200	675	3.03	1.03
1	26.0	17900	35800	71600	924	3.58	1.25
<b>GRADE 43 (HIGH TEST)</b>							
1/4	7.0	2600	3750	7500	66.1	1.24	0.38
5/16	8.0	3900	4900	9700	86.0	1.29	0.44
3/8	10.0	5400	7600	15200	148	1.38	0.55
1/2	13.0	9200	12900	25700	242	1.79	0.72
<b>GRADE 70 (TRANSPORT)</b>							
1/4	7.0	3150	6100	12100	66.1	1.24	0.38
5/16	8.7	4700	9400	18800	104	1.29	0.44
3/8	10.0	6600	12400	24700	142	1.38	0.55

**FIT STRIVES FOR EXCELLENCE**

All safety chain and attachments meets or exceeds SAE J684 Standards

**205**

All safety chain, attachments, and tie downs have been tested for ultimate strength capacities



NACM 96 CHAIN								
Nom. Size		Material Dia.		Wrk. Load Limit (Max.)	Proof Load (Min.)	Min. Break. Load	Ins. Length (Max.)	Ins. Width (Min.)
inch	mm	inch	mm	lbs			inch	inch
<b>GRADE 30 (PROOF COIL)</b>								
1/8	4.0	0.156	4.0	400	800	1600	0.94	0.25
3/16	5.5	0.217	5.5	800	1500	3200	0.98	0.30
1/4	7.0	0.276	7.0	1300	2600	5200	1.24	0.38
5/16	8.0	0.331	8.4	1900	3800	7600	1.29	0.44
3/8	10.0	0.394	10.0	2650	5300	10600	1.38	0.55
7/16	11.9	0.468	11.9	3700	7400	14800	1.64	0.65
1/2	13.0	0.512	13.0	4500	9000	18000	1.79	0.72
5/8	16.0	0.630	16.0	6900	13800	27600	2.20	0.79
3/4	20.0	0.787	20.0	10600	21200	42400	2.78	0.98
7/8	22.0	0.866	22.0	12800	25600	51200	3.03	1.08
1	26.0	1.020	26.0	17900	35800	71600	3.58	1.25
<b>GRADE 43 (HIGH TEST)</b>								
1/4	7.0	0.276	7.0	2600	3900	7800	1.24	0.38
5/16	8.7	0.343	8.7	3900	5850	11700	1.29	0.44
3/8	10.0	0.406	10.3	5400	8100	16200	1.38	0.55
7/16	11.0	0.468	11.9	7200	10800	21600	1.64	0.65
1/2	13.0	0.531	13.5	9200	13800	27600	1.79	0.72
5/8	16.0	0.630	16.0	13000	19500	39000	2.20	0.79
3/4	20.0	0.787	20.0	20200	30300	60600	2.76	0.98
7/8	22.0	0.866	22.0	24500	36750	73500	3.03	1.08
<b>GRADE 70 (TRANSPORT)</b>								
1/4	7.0	0.281	7.0	3150	6300	12600	1.24	0.38
5/16	8.7	0.343	8.7	4700	9400	18800	1.29	0.44
3/8	10.0	0.406	10.3	6600	13200	26400	1.38	0.55
<b>QUALITY IMPORTED SAFETY CHAIN</b>								